



you can



Network Print, Copy, Scan in Colour and Fax* for Superior Quality with Built-in Wi-Fi*.

Share professional colour quality output and functionality via a wireless* or Ethernet network. This easy to use device is a total colour communications centre for small businesses.

Key features

- Compact network ready colour laser All-in-One: print, copy, scan and fax*
- Connect to network via Wi-Fi*
- 8 ppm/cpm in colour, 12 ppm/cpm in mono
- Up to 2400 x 600 dpi print resolution
- Superior colour imaging technologies for crisp text and vibrant colours
- No waiting with Quick First-Print technologies
- Solution keys for easy scanning and eco copying
- Easy scan to network and to USB memory key
- User friendly 5-line LCD display
- 50-sheet ADF, 150-sheet cassette
- Energy efficient only 2.2 watts in sleep mode
- Convenient All-in-One colour cartridges

What's in the Box

Main unit, Cartridge 716 starter C/M/Y/K, power cord, quick setup guide, Shortcut key label, user software and manual CDs.

Dimensions (WxDxH)

430 mm x 484 mm x 429 mm

Supported OS

Windows 2000 / Server 2003 / Server 2008 / Server 2008 R2 / XP / Vista/ 7 Mac OS 10.4.9 - 10.7.x (Web distribution only)

Linux (Web distribution only)













* MF8080Cw only





Specifications





1 Flatbed & 50-sheet ADF 2 5-line LCD display 3 150-sheet cassette 4 Cartridge 716: 4 cartridges available: Black, Cyan, Magenta and Yellow

PRINTER Print speed Printing method Print quality Print resolution First Print Out Time Printer languages Print margins Toner saver mode Printing from memory media	Up to 8 ppm colour (A4) Up to 12 ppm mono (A4) Colour laser beam printing Up to 2400 x 600 dpi with Automatic Image Refinement 600 x 600 dpi Colour aprox: 28.5 seconds or less Mono aprox: 22 seconds or less UFRII-LT 5 mm-top, bottom, left and right 10 mm-top, bottom, left and right Yes Supported memory media USB memory key Supported file types: JPEG, TIFF
COPIER Copy speed First Copy Output Time (FCOT) Copy resolution Copy modes Multiple copy Reduction / Enlargement Toner saver mode Other features	Up to 8 cpm colour (A4) Up to 12 cpm mono (A4) Colour Approx. 29.3 seconds or less Mono Approx. 22.5 seconds or less Up to 600 x 600 dpi Text/Photo/Map (Default),Text/Photo/Map (quality), Printed Image, Text Up to 99 copies 25-400% in 1% increments No Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy
SEND FUNCTIONS Scan to USB memory key File formats	Yes PDF, JPEG, TIFF
SCANNER Type Scan resolution Colour scanning depth Greyscales Compatibility Max. scan width	Colour Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi 24 bit/24 bit (input/output) 256 levels TWAIN , WIA 216 mm
FAX° Modem speed Receive mode Fax resolution FAX memory Speed dials Group dials/destinations Sequential broadcast Memory backup Other features Fax only applies to MF8080Cw	Super G3 33.6kbps (Up to 3 seconds/page1) Fax only, Fax/Tel Auto Switch, Answer Mode, Manual RX Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi Ultra fine: 400 x 400 dpi Up to 512 pages1 Max. 139 Max. 131 Max. 199 dials / Max. 199 destinations Max. 210 locations 5 mins Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only) DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports
MEDIA HANDLING	

INTERFACE & SOFTWARE Interface type Operating System compatibility Software and printer management	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX, Wireless 802.11b/g ^o Windows 2000/Server 2003 ³ / Server 2008 ³ /Server 2008 R2 ³ / XP/ Vista/ 7 Mac OS X version 10.4.9- 10.7.x ² Linux ⁴ Presto! Page Manager, MF Toolbox, Remote User Interface (RUI), Department ID Management
GENERAL FEATURES Duty cycle Warm-up Time Memony Control panel Dimensions with trays (W x D x H) Installation space (W x D x H) Weight Operating environment Power Source Power Consumption	Max. 30,000 pages per month Approx. 30 seconds from power on 128MB (shared) 5 lines backlit LCD 430 mm x 484 mm x 429 mm 674 mm x 1229 mm x 801 mm Approx. 26 Kg Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240V(±10%) 50/60Hz (±2Hz) Maximum: Approx. 900 W Standby: Approx. 15 W Sleep mode: Approx. 2.2 W 5 Typical Electricity Consumption (TEC): 0.60 kWh/week Sound Power 6: Active: 63.4 dB(A) or less Standby: 43 dB(A) or less Sound Pressure 6: Active: 47 dB(A) or less Standby: inaudible
CONSUMABLES Cartridges	Cartridge 716 Black (2,300 pages ⁷) ⁸ Cartridge 716 Cyan (1,500 pages ⁷) ⁸ Cartridge 716 Magenta (1,500 pages ⁷) ⁸ Cartridge 716 Yellow (1,500 pages ⁷) ⁸
ACCESSORIES/OPTIONS Items	TEL 6 KIT LONG CORD (Telephone handset) ⁹
Standard disclaimers. All specifications	subject to change without notice

ndard disclaimers. All specifications subject to change without notice
Based on ITU-T Standard Chart No. 1
Web distribution only. Driver release November 2011
Network scanning not supported
Web distribution only. Linux support printing only. Driver release January 2012
When in wireless mode, consumption will be 2.7W
Declared noise emission in accordance with ISO 9296

Standard disclaimers. All specifications subject to change without notice

[1] Based on ITU-T Standard Chart No. 1

[2] Web distribution only. Driver release November 2011

[3] Network scanning not supported

[4] Web distribution only. Linux support printing only. Driver release January 2012

[5] When in wireless mode, consumption will be 2.7W

[6] Declared noise emission in accordance with ISO 9296

[7] Based on ISO/IEC 19798

[8] Printer ships with 800 pages CMYK (Cyan, Magenta, Yellow and Black) starter cartridges

[9] MF8080Cw only

MEDIA HANDLING

Scanner type Paper input (Standard) Flatbed and Automatic Document Feeder (ADF)

150-sheet cassette 1-sheet manual feed slot 50-sheet ADF

Paper output Media types 125-sheet

Plain paper, Recycled paper, Heavy Paper, Transparency, Coated Paper,

Label, Index card, Envelope

Media sizes

A4, A5, B5, Legal, Letter, Executive, Statement, Postcard, Foolscap, Envelope (COM10, Monarch, DL, ISO-C5, ISO-B5), Custom sizes: Width 76.2 to 215.9 mm; Length 127.0 to 355.6 mm.

A4, A5, B5, Legal, Letter, Executive, Statement, Postcard, Foolscap, Finelope (COM10, Monarch, DL, ISO-CS, ISO-B5), Custom sizes: Width 76.2 to 215.9 mm; Length 127.0 to 355.6 mm.

A4, A5, B5, B6, Legal, Letter, Statement, Custom sizes (W x L): Max 215.9 mm x 355.6 mm Min. 128 mm x 139.7 mm)

Cassette: 60 to 220 g/m² Manual feed slot: 60 to 220 g/m² ADF: 50 to 105 g/m²



















Canon Inc. canon.com

Canon Europe canon-europe.com

English Edition © Canon Europa N.V., 2011



Media weights