



System Specifications	WorkCentre 6515N	WorkCentre 6515DN	WorkCentre 6515DNI
One-sided Speed 8.5 x 11 in. 8.5 x 14 in. / 216 x 356 mm A4 / 210 x 297 mm	Up to 30 ppm Colour and Black and White Up to 24 ppm Colour and Black and White Up to 28 ppm Colour and Black and White		
Two-sided Speed 8.5 x 11 in. 8.5 x 14 in. / 216 x 356 mm A4 / 210 x 297 mm	NA	Up to 18 ppm Colour and Black and White Up to 17 ppm Colour and Black and White Up to 19 ppm Colour and Black and White	
Monthly Duty Cycle ¹	Up to 50,000 pages / month		
Recommended Average Monthly Print Volume ²	Up to 3,000 pages		
Processor	1.05 GHz		
Memory	2 GB		
Connectivity	10/100/1000Base-T Ethernet High-Speed USB 3.0		10/100/1000Base-T Ethernet High-Speed USB 3.0 Wi-Fi 802.11n Wi-Fi Direct®
Paper Handling			
Document Feeder			
Capacity ³	Single-pass Duplex Automatic Document Feeder (DADF): 50 sheets		
Sizes	Custom Sizes: 5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mm		
Weights	16 lb. bond to 45 lb. cover / 60 to 125 gsm		
Bypass Tray			
Capacity ³	50 sheets		
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm		
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm		
Media Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled		

Tray 1			
Capacity ³	250 sheets		
Sizes	Custom Sizes 3 x 5.8 in. to 8.5 x 14 in. / 76 x 147 mm to 216 x 356 mm		
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm		
Media Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled		
Optional Tray 2			
Capacity ³	550 sheets		
Sizes	Custom Sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 191 mm to 216 x 356 mm		
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm		
Media Types	Bond Plain Card Stock Custom Glossy Card Stock Hole punched Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled		
Total Capacity			
Device Standard Capacity ³	300 sheets		
Device Total Capacity ³	850 sheets		
Paper Output			
Output Capacity ³	150 sheets		
Automatic 2-Sided	NA Standard		
Device Specifications			
Electrical Requirements			
North America	Voltage: 120 VAC +/- 10 % Frequency: 60 Hz +/- 3 Hz, 12A		
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50 Hz +/- 3 Hz, 6A		
Power Consumption			
Operation ⁴	120V: Maximum 350 watts 220V: Maximum 370 watts		
Standby Mode ⁴	120V: Maximum 51 watts 220V: Maximum 52 watts		
Power Off Mode ⁴	120V: Maximum 0.2 watts 220V: Maximum 0.3 watts		
Sleep Mode ⁴	120V: Maximum 1.1 watts 220V: Maximum 1.2 watts		
Warm-up (from Sleep Mode)	As fast as 27 seconds		

Operating Environment			
Required Temperature Range Storage Operating	-4°F to 104°F / -20°C to 40°C 41°F to 90°F / 5°C to 32°C		
Required Relative Humidity	15% to 85%		
Sound Power Levels Operating Standby	6.84 B or less 4.25 B or less		
Sound Pressure Levels Operating Standby	52.5 dB(A) or less 26.3 dB(A) or less		
Dimensions and Weights (unpacka	nged)		
Workcentre 6515N, DN and DNI	Width: 16.5 in. / 420 mm Depth: 19.9 in. / 506 mm Height: 19.7 in. / 500 mm Weight: 67.7 lb. / 30.7 kg		
550-sheet Paper Tray	Width: 16.5 in. / 420 mm Depth: 18.3 in. / 465 mm Height: 5.9 in. / 150 mm Weight: 14.8 lb. / 6.7 kg		
Dimensions and Weights (package	ed)		
Phaser 6510N, DN and DNI	Width: 25 in. / 634 mm Depth: 22.8 in. / 580 mm Height: 26 in. / 659 mm Weight: 79.8 lb. / 36.2 kg		
550-sheet Paper Tray	Width: 21.1 in. / 535 mm Depth: 23 in. / 584 mm Height: 9.8 in. / 248 mm Weight: 18.7 lb. / 8.5 kg		
System Certification/Regulatory C	ompliance		
Certifications	c TUV us FCC 47CFR15-B ICES/NMB-3 "A" CE NOM EAC UkrSepro BIS GS FCC 47CFR68 ISED DC-01 Citrix™ Certified Cerner Apple [®] AirPrint [®] certification Google Cloud Print [™] Certification Mopria [®] certified Wi-Fi Alliance Certified Blue Angel MEDITECH ECOLOGO [®] EPEAT (United States) ENERGY STAR [®] To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.		
Сору			
Document Scanner	Single-pass Duplex Automatic Document Feeder (DADF) with 50-sheet capacity		
Document Scanner Size	Platen: Up to 8.5 x 11.7 in / A4 DADF: 8.5 x 14 in. / 216 x 356 mm		
Simplex Speed	Black and White: Up to 21 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm Color: Up to 13 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm		
Duplex Speed	Black and White: Up to 9 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm Color: Up to 8 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm		

First-Copy-Out Time	As fast as 12 seconds from the Platen	
Sides (input:output)	1:1, 1:2, 2:2, and 2:1	
Quantity	1 to 999	
Resolution	Up to 600 x 600 dpi	
Reduction/Enlargement	Variable zoom from 25 % to 400 % in 1 % increments	
Concurrency	Concurrent scanning and printing	
Copy Features	Automatic Background Suppression	
	Book Copying Book Copying with Centre Erase Collation Darkness Control Edge Erase ID Card Copy N-up Reduce/Enlarge (25 % -400 %) Image Shift Original Type Sample Copy Sharpness	
Print		
First-print-out Time	As fast as 12 seconds Colour and Black and White	
Print Resolution	Up to 1200 x 2400 dpi	
Page Description Languages	Adobe® PostScript® 3™ PCL® 5e, 6 PDF TIFF	
Maximum Print Area	4 mm edge of paper	
Print Features	Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS	
Operating Systems	Windows [®] , 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2, Server 2012 Mac OS [®] version 10.10 and higher Citrix [®] Redhat [®] Enterprise Linux [®] IBM [®] AIX [®] 5 HP-UX [®] 11iv2 Oracle [®] Solaris 9, 10 Fedora Core 12-15 SUSE [®]	
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD SMB SMTP, Secure SMTP LDAP, Secure LDAP Bonjour® / AirPrint® FTP Most protocols not in use can be disabled	
	Bonjour® / AirPrint® FTP	

Font Capability	136 PostScript fonts 88 PCL fonts	
Mobile Solutions and Mobile Devi	ce Apps	
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox [®] devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox [®] and non-Xerox [®] devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web- connected device.	
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox [®] Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play [™] store.	
Xerox® Mobile Link App (Free at Google Play™ Store and Apple® App Store)	The Xerox [®] Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox [®] multifunction printer.	
Xerox® Wireless Print Solutions Adapter (Optional)	The Xerox [®] Wireless Print Solutions Adapter seamlessly connects your Xerox [®] printer or MFP to modern mobile and desktop workflows, regardless of your office environment. For more information, visit www.xerox.com/WPSA	
Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service	Xerox [®] Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.	
Scan		
Capability	Colour and Black-and-white	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs	
Input Speed - Black and White	Scan up to 37 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	
Input Speed - Colour	Scan up to 21 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	
Resolution	Optical – 600 x 600 dpi	
Bit Depth	24-bit Colour / 8-bit Greyscale	
Maximum Scan Area	Platen: Up to 8.5 x 11.7 in. / A4 Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm	
Network Filing Protocol	FTP SMTP SMB/SMB2	
File Formats	JPG Single-page and Multi-page TIFF PDF Searchable PDF with integrated OCR	
Scan Driver Compatibility	WIA TWAIN	

Supported Scan Destinations	Scan to Email (local address book or LDAP integration) Scan to Network (via FTP/SMB) Scan to USB Memory Device Scan to USB Memory Device Scan to Email (SMTP) Scan to WSD Scan to Application (TWAIN Network) Scan to Application (TWAIN Network) Scan to MIA (WSD Scan) Scan to Mac 10.9 or later (Network/Mac ICA) Scan to Network Computer (SMB/FTP) Scan to Multiple Destinations in a Single Scan Job	
Security Features	Simultaneous HTTP and HTTPS support IPsec 802.1x Authentication S/MIME IP Filtering Secure Print Secure Fax Receive SNMP v3 LDAP (SASL) Network Authentication Kerberos Authentication (Unix / Linux / Windows ADS)	
Fax⁵		
Fax Speed	33.6 Kbps	
Memory	4 MB	
Resolution	Up to 400 x 400 dpi	
Compression	MH/MR/MMR/JBIG	
Fax Features	Broadcast Sending (up to 200 destinations) Delayed Start (up to 24 hours) Fax Address Book (up to 200 speed dials) Fax Forward to Email Fax Forwarding and Local Print Polling Receive Reject Junk Fax Secure Fax Receive	
Device Management		
Xerox [®] CentreWare [®] Web	 A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 	
Xerox [®] Embedded Web Server - Ir	ntegrated Device Web Page	
Device Status	Tray status/contents Consumables status Billing/Usage Quick Links	
Job Submission	Print-ready files (PS, PCL®, PDF, XPS, JPEG)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device.	
Browsers	Microsoft [®] Internet Explorer 11 Microsoft Edge [™] 38 Mozilla [™] Firefox [®] 48 Apple [®] Safari [®] 9.1 Google Chrome [™] 52	
Remote Print Services		
Xerox [®] MeterAssistant [®] Service	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox [®] device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Xerox® SuppliesAssistant® Service	Automatically orders supplies for Xerox [®] output devices based on actual usage, eliminating the need to manually manage supplies inventory.	

Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.		
What's In The Box			
	 WorkCentre 6515 Colour Multifunction Printer Standard Capacity Print cartridge: One of each (Cyan, Magenta, Yellow: 1,000 print capacity⁶; Black: 1,500 print capacity⁶ Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord Fax cord 		
Supplies and Accessories	Quantity	Part Number	
Supplies			
Extra-High Capacity Print Cartridges	Cyan: 4,300 standard pages ⁶ Magenta: 4,300 standard pages ⁶ Yellow: 4,300 standard pages ⁶	106R03693 106R03694 106R03695	
High Capacity Print Cartridges	Black 5,500 standard pages ⁶ Cyan: 2,400 standard pages ⁶ Magenta: 2,400 standard pages ⁶ Yellow: 2,400 standard pages ⁶	106R03488 106R03485 106R03486 106R03487	
Standard Capacity Print Cartridges	Black: 2,500 standard pages ⁶ Cyan: 1,000 standard pages ⁶ Magenta: 1,000 standard pages ⁶ Yellow: 1,000 standard pages ⁶	106R03484 106R03481 106R03482 106R03483	
Drum Cartridges	Black: 48,000 pages ⁷ Cyan: 48,000 pages ⁷ Magenta: 48,000 pages ⁷ Yellow: 48,000 pages ⁷	108R01420 108R01417 108R01418 108R01419	
Waste Cartridge	30,000 pages ⁷	108R01416	
Accessories			
550-sheet Paper Tray		097S04765	
Wireless Network Adapter497H		497K16750	

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 ² Expected regular monthly throughput.
 ³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
 ⁴ Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.
 ⁵ Requires analogue phone line.
 ⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print
 ⁷ Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com

