

Flexible, All-in-One
solution for small,
busy workgroups

i-SENSYS MF5940dn **i-SENSYS** MF5980dw

you can



High performance and energy efficient, Wi Fi* Laser Multifunction Printer.

Improve productivity thanks to powerful SEND functionality and auto duplexing features. This compact, network ready, multifunctional is highly energy efficient, keeping costs down.

Key features

- Compact laser All-in-One: print, fax, copy and scan
- Network ready with Remote User interface, PCL5e/6 and PostScript* support
- Connect to network via Wi-Fi*
- 33 ppm mono printing and copying
- First Copy Out Time: 8 seconds or less
- Superior copy image quality, up to 1200 x 600 dpi print resolution
- No waiting with Quick First-Print technologies
- Fast automatic double-sided printing, copying, scanning & faxing
- Solution keys for easy scanning, eco copying and secure print
- SEND functionality; scan to email, network folder & USB memory key
- User friendly 5-line LCD display
- 50-sheet Duplex Automatic Document Feeder
- 250-sheet cassette, 50-sheet multi-purpose tray & optional 500-sheet cassette (max. A4)
- Energy efficient – only 3 watts in sleep mode
- Convenient All-in-One cartridges

What's in the Box

Main unit, Cartridge 719, power cord, quick setup guide, guide, user software and manual CDs.

Dimensions (WxDxH)

390 mm x 473 mm x 431 mm

Supported OS

Windows 2000/ Server 2003/ Server 2008/ XP/ Vista/ 7

Mac OS X Version 10.4.9-10.7.x
(Web distribution only)

Linux (Web distribution only)



PRINT



COPY



FAX



SCAN

* MF5980dw only.

Canon

Specifications



- 1 Flatbed and DADF
- 2 50-sheet multi-purpose tray
- 3 250-sheet tray
- 4 Cartridge 719:
Optional Cartridge 719H

<p>PRINTER ENGINE</p> <p>Print speed Printing method Print quality Print resolution Double sided printing Printer languages Fonts Print margins Toner saver mode Printing from memory media</p>	<p>Up to 33 ppm (A4) Monochrome laser beam printing Up to 1200 x 600 dpi with Automatic Image Refinement 600 x 600 dpi Automatic UFR II-LT, PCL5e, PCL6, (PostScript Level-3 emulation³) 45 scalable, 10 bitmap (PCL) 5 mm-top, bottom, left and right Yes Supported memory media USB memory key Supported file types: JPEG, TIFF</p>
<p>COPIER</p> <p>Copy speed First Copy Output Time (FCOT) Copy resolution Copy modes Double sided copying Multiple copy Reduction / Enlargement Toner saver mode Other features</p>	<p>Up to 33 cpm (A4) Approx. 8 seconds or less Up to 600 x 600 dpi Text, Text/Photo, Text/Photo+, Photo 2-sided to 2-sided (Automatic) Up to 99 copies 25-400% in 1% increments Yes Collate, 4 on 1, ID Card Copy</p>
<p>SEND FUNCTIONS</p> <p>Scan to file server Scan to E-mail Scan to USB memory key File formats</p>	<p>SMB SMTP, POP3 Yes TIFF (B&W), JPEG, PDF, PDF (Compact)</p>
<p>SCANNER</p> <p>Type Scan resolution Colour scanning depth Greyscales Compatibility Max. scan width</p>	<p>Colour Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi 24 bit/24 bit (input/output) 256 levels TWAIN, WIA 216 mm</p>
<p>FAX</p> <p>Modem speed Receive mode Fax resolution FAX memory Speed dials Group dials/destinations Sequential broadcast Memory backup Double sided faxing Other features</p>	<p>Super G3 33.6kbps (Up to 3 seconds/page¹) Fax only, Fax/Tel Auto Switch, Answer Mode, Manual Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi Up to 512 pages¹ Max. 200 (including 19 one-touch dials) Max. 199 dials/ Max.199 destinations Max. 210 locations 1 hour Yes (Transmit and Receive) Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only)</p>
<p>MEDIA HANDLING</p> <p>Scanner type Paper input (Standard) Paper input (Option) Paper output Media types Media sizes Media weights</p>	<p>Flatbed and Duplex Automatic Document Feeder (DADF) 250-sheet cassette 50-sheet multi-purpose tray 50-sheet DADF 500-sheet cassette 150-sheet Plain paper, Recycled paper, Heavy paper, Transparency, Label, Envelope, Bond paper, Postcard, Indexcard Cassette and optional cassette: A4, A5, B5, Legal, Letter, Executive Multi-purpose tray: A4, A5, B5, Legal, Letter, Executive, STMT, Postcard, Indexcard, Envelope (COM10, Monarch, DL, ISO-C5, ISO-B5), Custom sizes: Width 76 to 216 mm; Length 127 to 356 mm. DADF: One-sided scanning: A4, A5, Legal, Letter, STMT, B5, B6 Custom sizes (W x L): Max 215.9 mm x 355.6 mm Min. 128 mm x 139.7 mm Two-sided scanning: A4, A5, Legal, Letter, B5, B6 Cassette and optional cassette: 60 to 128 g/m² Multi-purpose tray: 60 to 190 g/m² DADF: One-sided scanning: 50 to 105 g/m², Two-sided scanning: 64 to 105 g/m²</p>

<p>INTERFACE & SOFTWARE</p> <p>Interface type Operating System compatibility Software and printer management</p>	<p>USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX, (Wireless 802.11b/g³) Windows 2000/ Server 2003/ Server 2008/ XP/ Vista/ 7 Mac OS X Version 10.4.9-10.6.x^{2,3} Linux⁴ Presto! Page Manager, MF Toolbox, Remote User Interface (RUI), Department ID Management</p>
<p>GENERAL FEATURES</p> <p>Duty cycle Warm-up Time Memory Control panel Dimensions with trays (W x D x H) Installation space (W x D x H) Weight Operating environment Power Source Power Consumption Noise Levels</p>	<p>Max. 15,000 pages per month Approx. 11 seconds or less from power on 256 MB (shared) 5 lines BW LCD 390 mm x 473 mm x 431 mm 672 mm x 1279 mm x 931 mm (with the optional paper cassette and optional handset attached) Approx 19.1 Kg Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep mode: Approx. 2.3 W⁵ Typical Electricity Consumption (TEC): 1.4 kWh/week Sound Power⁶ Active: 70.6 dB(A) or less Standby: 43.0db(A) or less Sound Pressure⁶ Active: 53.0 dB(A) or less Standby: Inaudible</p>
<p>CONSUMABLES</p> <p>Cartridges</p>	<p>Cartridge 719 (2,100 pages⁷) Cartridge 719 H (6,400 pages⁷)</p>
<p>ACCESSORIES/ OPTIONS</p> <p>Items</p>	<p>PAPER FEEDER PF-44 (500-sheet cassette) TEL 6 KIT LONG CORD (Telephone handset)</p>
<p>Standard disclaimers. All specifications subject to change without notice. [1] Based on ITU-T Standard Chart No. 1 [2] Web distribution only. Driver release November 2011 [3] Network scanning not supported [4] Web distribution only. Linux support printing only. Driver release January 2012 [5] When in wireless mode, consumption will be 3W [6] Declared noise emission in accordance with ISO 9296 [7] Based on ISO/IEC19752 [8] MF5980dw only</p>	

