

FS-1350DN

► print ► copy ► scan ► fax


A4 MONOCHROME DESKTOP PRINTER

HIGH- PERFORMANCE DESKTOP PRINTING

The new KYOCERA FS-1350DN is a network ready device that gives you the powerful performance you need at the specified speeds. The highest security standards prevent data interception or misuse and the high paper capacity ensures smooth uninterrupted workflows. Furthermore, the easy-to-understand LCD control panel makes this device especially user-friendly when used by several persons simultaneously.

- Up to 30 pages per minute with 1,200 dpi resolution
- Standard duplex unit for double-sided printing
- Max. paper capacity of up to 800 sheets
- Powerful controller with 128 MB RAM as standard (max: 1,152 MB)
- USB and network connectivity as standard
- Highly reliable thanks to long-life components
- Backlit LCD display
- Exceptionally low printing costs in its class

Standard network connectivity with the highest security standards for safe communication with the printer.



Easy-to-understand LCD display for exceptional ease of use.



FS-1350DN

A4 MONOCHROME DESKTOP PRINTER



ECOSYS stands for ECOlogy,
ECOnomy and SYStem-printing.

With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

PRESCRIBE IIe

With the KYOCERA page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

The KM NetViewer

The KM NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

Status Monitor and Command Center

The Status Monitor shows the current printers condition and gives direct access to the Command Center for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

USB Host Interface for USB Flash Memory

PDF files can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. Documents are selected directly via the printer's control panel. No computer is required.

General

Technology

Kyocera ECOSYS, Laser

Engine speed

Up to 30 pages per minute A4

Resolution

1,200 x 1,200 dpi

Time to first page

6 seconds or less

Warm-up time

14 seconds

Duty cycle

Max. 20,000 pages per month,
average 2,000 pages per month

Power source

AC 220 ~ 240 V, 50/60 Hz

Power consumption

Printing: 484 W
Stand-by: 12 W
Power-Saving (ECOpower): 7.1 W

Noise (ISO 7779)

Printing: 54 dB(A)
Stand-by: 30 dB(A)

Power-Saving (ECOpower)

Immeasurably low

Dimensions (W x D x H)

375 x 393 x 267 mm

Weight

Main unit incl. toner: Approx. 12 kg

Certifications

TÜV/GS, CE

This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Paper Handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

250-sheet universal paper cassette, 60-120 g/m², A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm to 216 x 297 mm)
50-sheet multi-purpose tray, 60-220 g/m², A4, A5, A6, B5, Letter, Custom (70 x 148 mm to 216 x 356 mm)
Max. paper capacity incl. options: 800 sheets
Duplex as standard

Output capacity

250 sheets face-down

Controller

Processor

PowerPC-440F5-500 MHz

Memory

Standard 128 MB + ECOMemory, max. 1,152 MB in 1 DDRII SDRAM DIMM slot

Standard interface

USB 2.0 (Hi-Speed), Fast Ethernet 10Base-T/100Base-TX, KUJO/W interface slot, USB Host - USB 1.1, Slot for optional CompactFlash®-Card

Emulations

PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible) with automatic emulation switching, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, PDF - 1.5

Controller language

Prescribe IIe

Fonts

101 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417

Downloadable fonts

Kyocera, PCL + TrueType format, Type 1 + 3 format

Print features

Automatic duplex unit enables booklet Printing

Consumables

TK-130 Toner-kit

Microfine toner for 7,200 pages in accordance with ISO/IEC 19752*

*Capacity of starter toner is 3,600 pages in accordance with ISO/IEC 19752

Options

PF-100 Paper feeder (max. 2 units)

250 sheets, 60-120 g/m², A4, A5, A6, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 297 mm)

CB-100 Cabinet

Wooden desk with storage capacity, including castors (wheels)

Memory upgrade

MDDR2-128: 128 MB; MDDR2-256: 256 MB;
MDDR2-512: 512 MB, MDDR2-1024: 1,024 MB

CompactFlash®-Card

1 slot (up to 4 GB)

USB Flash Memory

Supports PDF direct printing via USB Host Interface

Optional interface

PS159: Wireless LAN (802.11b/g)

PS1109 Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45)

PS129 Fibre Optic: 100BaseSX (SC)

PS1129 Gigabit Fibre Optic: 1000BaseSX (SC)

Model variations

FS-1350DN/KL3

FS-1350DN incl. warranty extension KYOLife 3 years

Warranty

2-year warranty as standard. KYOCERA guarantees the drums and developers for 3 years or maximum 100,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

KYO LIFE The up to 3-year on-site warranty extension for printer and options.



Your KYOCERA Business Partner:

KYOCERA MITA Europe B.V. - Branch Office Germany - Otto-Hahn-Straße 12 - 40670 Meerbusch - Germany
Tel +49 (0) 2159 928-500 - Fax +49 (0) 2159 918-100
www.kyoceramita-europe.com - info@kyoceramita-europe.com

KYOCERA MITA Corporation - 2-28, 1-Chome - Tamatsukuri - Chuo-Ku
Osaka 540-8585 - Japan - www.kyoceramita.com

* KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. KYOcount is a trademark of KYOCERA MITA Europe B.V.



Product depicted includes optional extras.

KYOCERA