

SP 3710 multifunction solution specifications

The SP 3710 series combines high performance, with low total cost of ownership. These printers are low maintenance, and ideal for high productivity and multifunctional use. They are engineered for high reliability and are easy to use, with easy to set up optional 5GHz Wi-Fi.

Features for printers in this series include:

- Up to 32 pages per minute output
- Ultra-high yield 7,000 page toner cartridge in the box
- · Supports Air print, Google cloud print via mobile devices
- · Compact footprint saves on valuable office space
- · Optional WiFi capability and 250-sheet tray

SP 3710DN/SP 3710SF

MAIN SPECIFICATIONS

OFNEDAL	SP 3710DN		SP 3710SF
GENERAL			
Warm-up time (seconds) First output speed: B/W	26	7.5	30
(seconds) Continuous output speed (ppm)		32	
Memory: standard (MB)	128		256
Dimensions: W x D x H (mm)	370 x 392 x 262		405 x 392 x 420
Veight (kg)	13	00 040 \/ 50/00 -	18
Power source	2	20 - 240 V, 50/60 Hz	
COPIER			
Multiple copying	-		Up to 99 copies
Resolution	-		1,200 x 600 dpi
Zoom	-		From 25% to 400% in 1% steps
PRINTER			
Printer language: standard	PCL5e, PCL6, PostScript 3 (emulation)		
Print resolution: maximum (dpi)	1,200 x 1,200		
nterface: standard	Ethernet 10 base-T/100 base-TX, USB2.0 Type B		
nterface: option	Wireless LAN (IEEE 802.11 a/b/g/n/ac)		
Vindows® environments	Windows® 7/8.1/10, Windows® Server 2008/2012/2012R2/2016		
Mac OS environments	Macintosh OS X v10.10 or later		
Other supported environments	Linux environment		
SCANNER			
Scanning: B/W (ipm)	-		13
Scanning: full colour (ipm)	-		4.5
Resolution: maximum (dpi)	-		600
FAX			
Compatibility	-		ITU-T (CCITT) G3
Fransmission speed (seconds)	-		3
Modem speed: maximum (Kbps)	-		33.6
PAPER HANDLING			
Recommended paper size		A4, A5, A6, B5, B6	
Paper input: standard (sheets)		300	
Paper input: maximum (sheets)		550	
Paper output: standard (sheets)	125		50
Paper weight (g/m²)		52 - 162	
ECOLOGY			
Power consumption: max. (kW)		Less than 1.025	
Power consumption: sleep (W)	Less than 0.72		Less than 0.87
OPTIONS			
x 250-sheet paper tray			
CONSUMABLES			
Starter toner (prints)		7,000	
Toner (high yield) (prints)		7,000	
Consumable yield measuring method ISO/IEC 19752			













ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2018 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.



www.ricoh-europe.com