Xerox[®] AltaLink[®] Colour Multifunction Printers

Xerox[™]

C8130/C8135/C8145/C8155/C8170



AltaLink® C8100 Series Colour Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

System Specification	AltαLink [®] C8130	AltαLink [®] C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170		
Speed							
Colour/Black-and-White	Up to 30/30 ppm	Up to 35/35 ppm	Up to 45/45 ppm	Up to 55/55 ppm	Up to 70/70 ppm		
Monthly Duty Cycle ¹	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages	Up to 300,000 pages		
Hard Drive / Processor / Memory	Minimum 128 GB SSD / Opti	onal: 500 GB HDD / Intel® A	Atom™ Quad Core 1.91 GHz / 4	4 GB system memory (8 GB syst	em memory AltaLink C8170)		
Connectivity	Ethernet 10/100/1000 Base- (iBeacon)	Γ, High-speed USB 2.0 direct	t print, Wi-Fi/Wi-Fi Direct with	optional Xerox [®] Dual Band Wire	eless Kit, NFC, Bluetooth		
Controller Features	Unified Address Book, Remote	e Control Panel, Configuratio	on Cloning, Fleet Orchestrator,	Configuration Watchdog			
Optional Controller	Xerox® EX-c C8100 Print Serve	er Powered by Fiery®					
Copy and Print							
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; P	rint: Up to 1200 x 2400 dpi					
First-Print-Out Time (as fast as)	5.7 seconds colour/4.2 seconds black and white		4.9 seconds colour/3.8 seconds black and white	4.5 seconds colour/3.2 seconds black and white	3.8 seconds colour/3.0 seconds black and white		
First-Copy-Out Time (as fast as) (from platen/ warmed up state)	6.1 seconds colour/4.5 second	ds black and white	5.5 seconds colour/4.4 seconds black and white	4.7 seconds colour/3.7 seconds black and white	4.0 seconds colour/3.2 seconds black and white		
Page Description Language	Adobe® PostScript® 3™, Adob	e [®] PDF, PCL [®] 5c / PCL [®] 6	'		-		
Print Features		, Store and Recall Driver Set	tings, Bi-directional Real-time :	ncrypted Secure Print, Xerox® Ec Status, Scaling, Job Monitoring, Alternate Pages			
Mobile and Cloud Ready							
Mobile Connectivity	Near-Field Communication (N	NFC); Optional: Wi-Fi Direct	, Wi-Fi (802.11 b/g/n/ac), AirPi	rint (iOS) including iBeacon (Blu	etooth)		
Mobile Printing	AirPrint®, Mopria®, Xerox® Prii (iOS/Android), AirPrint (iOS) ii			erox App; Optional: Xerox [®] Wo	rkplace Mobile App		
Mobile Scanning	AirPrint; Optional: Xerox® Wo	orkplace Mobile App (iOS/An	droid)				
Mobile Apps and Xerox® App Gallery	Visit xerox.com/Workplace/	Automate everyday processes with apps that translate, redact, eSign, personalise print, convert, route, collaborate and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions)					
Xerox® Workplace Suite and Xerox® Workplace Cloud	print fleet, while enabling wo	rker productivity and mobilit	ty through a set of robust worl	omers time and money by provic kflows. Xerox enables ultimate co oud based-version (Workplace C	ustomer flexibility by offering		

Scan	
Standard Features	Destinations: Scan to USB / Email / Network (FTP/SMB), Scan to Cloud Repositories (Dropbox, One Drive and Google Drive) ² , HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan Preview, Scan to Home, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Password Protected PDF, Unified Address Book, Optical Character Recognition (OCR), Scan to Folder, 1-Touch Apps, TWAIN Support
Optional Features	Xerox® Scanning App for DocuShare®, other solutions available through various Xerox Business Innovation Partners at xerox.com/Software-Solutions
Fax	
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement, Fax Build Job
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share
Security	
Standard Features	802.1x, IPsec, HTTPS, SFTP and Encrypted Email, McAfee® Embedded Control Whitelisting, Firmware Verification, McAfee® ePolicy Orchestrator®, McAfee Enterprise Security Manager², LogRhythm SIEM², Splunk SIEM², Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TLS 1.1/1.2, Security Certificates utilizing ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, automated threat response through McAfee® DXL/Cisco® pxGrid integration, Local Authentication(Internal Database), FIPS 140-2.User Access and Internal Firewall, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, TPM, Trusted Boot Encrypted Storage Drive (AES 256-bit, FIPS 140-2), Job Level Encryption via HTTPS and Drivers, Signed Email Under evaluation for Common Criteria Certification (ISO 15408), Encrypted Secure Print
Optional Features	McAfee® Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET)³, Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with Image Overwrite, Xerox® Workplace Cloud/Suite Print Management and Content Security; learn more at xerox.com/WorkplaceSolutions
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at xerox.com/PrintManagement

Features and Accessories

Single-Pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of two-sided documents, up to 270 impression per minute (ipm).



USER INTERFACE



Intuitive Tablet-Like 10.1-inch Colour Touchscreen is

customisable and lets you perform tasks in just a few taps. Try it out at xerox.com/AltaLink8100UI.

PAPER INPUT⁴

П

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to A3 and Tray 2 handles media sizes up to SRA3.



Envelope Kit (optional – replaces Tray 1) provides feeding of up to 60 envelopes.



High-Capacity Tandem Tray Configuration holds a total paper capacity of up to 3,140 sheets.

Four-Tray Module Configuration (available for C8130/C8135) holds a total

(available for C8130/C8135) holds a total of up to 2,180 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 89 x 98 mm to 320 x 1,320 mm.





per capacity to 6,140

LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to $320 \times 1,320 \text{ mm}$ media.



INNOVATIVE TECHNOLOGIES



Xerox® Integrated RFID Card
Reader (optional) adds card-based
authentication with support for over
90 access cards



Near Field Communication (NFC) Tap-to-Pair allows users to tap their mobile device to the AltaLink C8100 Series user panel and quickly connect with the multifunction printer.



Smart Proximity Sensor detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.

PAPER OUTPUT / FINISHERS⁴



Office Finisher
(optional) provides
advanced finishing
functions, optional
crease/score and
saddle-stitch booklet,
making it capable of
60-page booklets
(2 to 15 sheets).



Business Ready
(BR) Finisher (optional) (options you advanced Z-finishing functions the at a great value.

BR



C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold and Z-half-fold to the BR Finisher or BR Booklet Maker Finisher.



BR Booklet Maker Finisher (optional) create 64-page saddle-stitched booklets (2 to 16 sheets).



Dual Offset Catch Tray (available when no finishers are installed; Single Offset Catch Tray with finishers).



Integrated Office Finisher (optional with C8130/C8135/ C8145/C8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



Convenience Stapler (optional) staples up to 50 sheets of 75 gsm media.

Device Specification						
Control Panel Languages		US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic				
Accessories						
Optional	Long-Sheet Feed kit (banner pri 500 GB HDD	equires Horizontal Transport Kit; irres Horizontal Transport Kit) C Vork Surface ⁵) lable AltaLink C8130, C8135, C er Powered by Fiery options, includes LAN Fax) and Wireless Kit element Kit eader Kit nown as Auxiliary Access Devicinting)	-fold / Z-fold Unit for BR Fir 8145, C8155) e) Interface for third-party	access control devices, such	as coin machines and card readers	
Electrical Requirements	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltαLink® C8170	
North America	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 1	5 A			Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 20 A	
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 1				Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 10 A	

Device Specification (continue	ed)				
Power Consumption	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltαLink® C8170
Running (Average)	115 V: 576 watts 230V: 586 watts	115 V: 600.3 watts 230V: 595.8 watts	115 V: 717 watts 230V: 674 watts	115 V: 806 watts 230V: 760 watts	115 V: 929 watts 230V: 908 watts
Standby Mode	115 V: 67 watts 230V: 71 watts	115 V: 64 watts 230V: 70 watts	115 V: 71 watts 230V: 71 watts	115 V: 72 watts 230V: 70.3 watts	115 V: 91.1 watts 230V: 79 watts
Auto Off/Sleep Mode	115 V: 0.69 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115 V: 0.69 watts 230V: 0.72 watts (Default time to sleep mode = 0 minutes)	115 V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115 V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115 V: 0.68 watts 230V: 0.75 watts (Default time to sleep mode = 0 minutes)
Warm-up (from Off)	As fast as 85 seconds				
Recovery from Sleep	As fast as 4.5 seconds				
Operating Environment					
Required Temperature Range	10 to 28 °C				
Required Relative Humidity	15% to 85%				
Sound Power Levels	Operating: 63.7 / 64.2 dB(A) Standby: 4.0 / 4.0 dB(A)	A)	Operating: 65.2 / 67.3 dB(A) Standby: 4.3 / 4.3 dB(A)		Operating: 70.4 dB(A) Standby: 4.3 dB(A)
Dimensions and Weight					
Base Configuration	Width: 620 mm Depth: 723 mm Height: 1,130 mm Weight: 143.1 kg	Width: 620 mm Depth: 793 mm Height: 1,169 mm Weight: 159.7 kg			
With Integrated Office Finisher (C8130, C8135, C8145, C8155)	Width: 819 mm Depth: 723 mm Height: 1,130 mm Weight: 154.2 kg				N/A
With Office Finisher (with Booklet Mαker)	Width: 1,207 mm Depth: 723 mm Height: 1,130 mm Weight: 182.5 kg				Width: 1207 mm Depth: 793 mm Height: 1,169 mm Weight: 199 kg
Base Configuration with Business Ready (BR) Finisher	Width: 1,395 mm Depth: 723 mm Height: 1,130 mm Weight: 187 kg				Width: 1,395 mm Depth: 723 mm Height: 1,169 mm Weight: 203.4 kg
Base Configuration with BR Booklet Maker Finisher	Width: 1,496.3 mm Depth: 723 mm Height: 1,130 mm Weight: 204 kg	Width: 1,496.3 mm Depth: 723 mm Height: 1,169 mm Weight: 220.6 kg			
Base Configuration with BR Booklet Maker Finisher and C-fold / Z-fold Unit	Width: 1,632 mm Depth: 723 mm Height: 1,130 mm Weight: 254.3 kg	Width: 1,632 mm Depth: 723 mm Height: 1,169 mm Weight: 270.9 kg			
Base Configuration with BR Booklet Maker Finisher, C-fold / Z-fold Unit and High Capacity Feeder	Width: 2,361 mm Width: 2,36 Depth: 723 mm Depth: 723 Height: 1,130 mm Height: 1,1 Weight: 285.2 kg Weight: 30				
System Certification / Regulat	ory Compliance				
Certifications	To view the latest list of cer	tifications, go to xerox.com/Of	ficeCertifications		

Paper Handling	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Single-pass Duplex Automat					
Capacity ⁴	130 sheets				250 sheets
Speed (Up to)	82 ppm black-and-white and 141 ipm black-and-white and				135 ppm black-and-white and colour (simplex) 270 ipm black-and-white and colour (duplex)
Paper Sizes Sensed	85 x 125 mm to 297 x 432 m	m			
Weights	60 to 128 gsm				
Bypass Tray (Standard)					
Capacity ⁴	100 sheets				
Sizes	Custom Sizes: 89 x 98 mm to	320 x 1320 mm (SEF); Op t	:ional: Long Sheet Feed Kit (Bai	nner Printing)	
Weights	52 to 300 gsm				
	Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Glossy Card Stock Plain Plain-Reloaded Preprinted Recycled Transparencies	ck ck Reloaded ded			
Trays 1 and 2 (Standard)					
Capacity ⁴	520 sheets each				
Sizes	Tray 1: Custom Sizes: 140 x 1 Tray 2: Custom Sizes: 140 x 1		EF)		
Weights	52 to 300 gsm				
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Plain Plain-Reloaded Preprinted Recycled Transparencies	ck ck Reloaded ded			

Paper Handling (continued)	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170				
Four Tray Module (Trays 3 an									
Capacity ⁴	Tray 3: 520 sheets Tray 4: 520 sheets								
Sizes	Trays 3 and 4: 140 x 182 m	Trays 3 and 4: 140 x 182 mm to SRA3 mm (SEF)							
Weights	52 to 300 gsm								
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stoch Heavyweight Glossy Card Stoch Heavyweight Glossy Card Stoch Heavyweight Glossy Card Stoch Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Glossy Card Stoch Lightweight Glossy Card St	ock ock Reloaded aded ck							
	Transparencies								
High Capacity Tandem Tray (
Capacity ⁴	Tray 3: 867 sheets Tray 4: 1,133 sheets								
Sizes	A4, JIS B5, Executive (7.25 x	10.5 in) LEF							
Weights	52 to 300 gsm								
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted	:k							
Envelope Tray (Optional – Re _l									
Capacity ⁴	Up to 60 envelopes								
Sizes	No. 10 Commercial (9.25 x 4 Custom Sizes: 98 x 148 mm								
Weights	75 to 90 gsm								
High-Capacity Feeder (HCF) (Optional with all models)								
Capacity ⁴	3,000 sheets								
iizes	Standard Sizes: A4 or B5 LEF								
Weights	52 to 300 gsm								
Total Capacity									
Device Total Capacity ⁴	Four Tray Module: 2,180 she Four-Tray Module with High- High-Capacity Tandem Tray High-Capacity Tandem Tray	Capacity Feeder: 5,180 shee Module: 3,140 sheets							

Finishing	AltaLink® C8130 Alta	aLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170			
Output Trays (Standard) (Du	al Offset Catch Trays not available	e with Integrated Office	Finisher and limited to one w	rith Office Finisher and BR Fini	shers)			
Stacking Tray Capacity ⁴	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face-up Tray: Up to 100 sheets							
Integrated Office Finisher (C	tional with AltaLink C8130/C8135/C8145/C8155)							
Stacking Tray Capacity ⁴	500 sheets of 80 gsm – A4 or 250 s	heets of 80 gsm – A3						
Sizes	89 x 98 mm to 297 x 432 mm							
Weights	52 to 300 gsm							
Stapling	Single / Dual Position Auto-Stapling: 50 sheets maximum: Letter / A4 / B 30 sheets maximum: Legal / Tabloid			vers)				
Office Finisher (Optional)								
Stacking Tray Capacity ⁴	2,000 sheets unstapled or 1,000 she	eets single stapled or 750 s	heets dual stapled (A4)					
Stacking Tray Sizes	210 x 182 mm to 297 x 432 mm							
Weights	52 to 300 gsm							
Multiposition Stapling	50 sheets maximum: Letter / A4 / B3 30 sheets maximum: Legal / Tabloid			vers)				
Hole Punch (Optional)	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch							
Booklet Maker for Office Fin	sher (Score/Crease, Saddle-stitch S	Staple) (Optional)						
Top Tray Capacity4	40 booklets (2-15 sheets per bookle	t – 80 gsm or less)						
Sizes	Letter – A4 SEF Legal – B4 SEF Tabloid – A3 SEF							
Saddle-Stitch Stapling	2-15 sheets / 8-60 page booklet 60 to 256 gsm							
Score / Crease	1-15 sheets / unstapled 60 to 105 gsm							
Business Ready (BR) Finisher	(Optional) (Requires Horizontal T	ransport Kit)						
Capacity ⁴	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets 100 sets (dual or 4-position stapling		sition staple) A4					
Sizes	100 x 148 mm x 320 x 488 mm for 182 x 203 mm to 320 x 488 mm fo B5 to A3 for stapling							
Weights	52 to 300 gsm							
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) Letter, Legal, Tabloid, A3, A4, B4 and	3						
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch							
BR Booklet Maker Finisher (0	Optional) (Requires Horizontal Trar	nsport Kit)						
Capacity ⁴	Offsetting Top Tray: 500 sheets of A Stacking Stapling Tray: 1,500 sheets of A4 / A3 unstapled of 200 stapled sets of A4 (single-positi dual or 4-position stapling) or 100 s	or on stapling or						
Sizes	100 x 148 mm x 320 x 488 mm for 182 x 203 mm to 320 x 488 mm fo B5 to A3 for stapling							
Weights	52 to 300 gsm							
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) Letter, Legal, Tabloid, A3, A4, B4 and							
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch							
Booklet maker	Saddle-stitch 2 to 16 sheets (7 shee Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 suppor	, and the second	ed or 5 sheets at 177 to 220 gs	m coated)				

Finishing (continued)	AltαLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170		
C-fold / Z-fold Unit (Optiona	with BR Finisher and BR Booklet Maker Finisher)						
Types	C-fold, Z-fold and Z-half-fold						
Capacity ⁶	40 sheets						
Sizes	C-fold and Z-fold: Letter – A4 S Z-half-fold: A3 only	EF only					
Weights	64 to 90 gsm						
Output Trays	Envelope Tray: C-fold, Z-fold ar Stacker Tray or Top Tray: Z-halt						
Convenience Stapler (Option	al - Includes Work Surface ⁵)						
Capacity ⁶	50-sheet stapling 5,000 staples Requires separate power outle	t					
Сору	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170		
First-Copy-Out Time (from platen/warmed up Colour/Black-and-White)	As fast as 6.1 seconds / As fast as 4.5 seconds		As fast as 5.5 seconds / As fast as 4.4 seconds	As fast as 4.7 seconds / As fast as 3.7 seconds	As fast as 4.0 seconds / As fast as 3.2 seconds		
Sides (input:output)	1-1, 1-2, 2-2, 2-1						
Quantity	1 to 9,999						
Resolution (max)	Up to 600 x 600 dpi						
Reduction / Enlargement	Variable zoom from 25% to 4	00% in 1% increments					
Concurrency	Program-ahead to allow a job	to be queued while the initial job	o is processed (Copy, Print, Fax o	ınd Scan)			
Copy Features	Authentication for Services (i.e. Auto Paper Select Auto Reduction & Enlargemen Auto Tray Switching Automatic 2-sided / Duplex Bc Build Job (enables page-level p Collation	t (to fit the selected paper size) poklet Creation programming and also lets you p ack, back only, printed inside and and graphic descriptions)	oroof each section or delete the	last section as the job is built)			
Xerox® Copier Assistant®	PC attached via the USB port,	vare provides a PC-based alterno this software supports text-to-sp nt. For more information or to do	eech, screen magnification and	easy PC keyboard access to bas			

Print	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Resolution (up to)	1200 x 2400 dpi				
Print Features	Cover Selection Delay Print (specific time) Us Image Options (Toner Saver, Job Identification (Print ID o LAN Fax (requires optional Fa Layout/Watermark N-up (up to 16 pages per sha Booklet Layout Long Sheet/Banner Finishing Fit to New Paper Size Hold All Jobs Paper Selection by Attribute Saved Job (colour jobs can b Secure Print with Timed Dele Special Pages (exception pa Store and Recall Driver Settir Sustainability Features (Xero Two-sided Printing (as defau	our by Words) Bi-directional Reser Permissions Resolution (Standard, Enhan r Banner, Print ID in margins ax Kit) Sample Set e printed as monochrome) etion ge programming: covers, inser	ced, High)) on first page only or all pages) rts, exception pages) ex, N-up, Turn-off Banner and I	Print ID, Smart Sample Set, Hold	All Jobs)
Print from USB					
Operating Systems	Windows Server 2008 SP2 (3 Windows Server 2018 R2 (64 Windows Server 2012 and 64-bit Windows Server 2019 (64-bit Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.13, 10.14, 10.15 Fedora® Core Ubuntu®	4-bit) 2 (64-bit) t) t)			
Network Protocols	TCP/IP: HTTP/HTTPS, Interno Microsoft Windows Network Bonjour® / AirPrint® IPv6 Most protocols not in use ca	ing over IP	Raw Socket Printing/Port 9100,	IPv4/IPv6, WSD	
Font Capability	PCL: 93 scalable fonts, line p	rinter and bitmap font (includ	ling Cyrillic font support) PostSo	ript 3: 173 Type 1 fonts, 2 Multip	ole Master fonts
Xerox® Globαl Print Driver®				x® and non-Xerox devices from a simplifying print services manag	
Xerox® Pull Print Driver	single driver. The Xerox® Pull	Print Driver extends convenie		gle driver in a Pull Print environm nting assets. IT administrators n os® and others.	
Unified Address Book for Fa	x, Internet Fax, Email and S	can to			
Features	Services supported: Fax, Inte Maximum contacts: 5,000 Contacts: Supports 1 or more Favourites for quick access of	e destinations			

Scan	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Concurrency	Scan while the system is p concurrent jobs)	rinting, copying or while it is tro	insferring scan-to-network or fa	c jobs (priority is for the return o	of scanned originals and printing
Input Speed (up to)	82 ppm black-and-white a 141 ipm black-and-white a				135 ppm black-and-white and colour (simplex) 270 ipm black-and-white and colour (duplex)
Resolution	72 x 72 dpi to 600 x 600 c	lpi			
Bit Depth	1-bit (black-and-white), 8-	bit (greyscale), 24-bit (colour)			
Maximum Scan Area	A3				
Scan Template Management	Support 250 scan templat Create Xerox® CentreWare		via device cloning to other mul	tifunction printers' confirmation	n sheet options
Network Protocols	SFTP, FTP, SMB, HTTP, HT	TPS			
File Compression		MH, G4 MMR compression – sir PDF/A-1b (MRC, JPEG, G3 MH,	ngle or multiple pages) G4 MMR, JBIG 2 Huffman, JBIG	ā Arithmetic Compression, Defle	ate (for black-and-white and
Document Management Fields (Metadata)	1 to 6 user-programmab Metadata field consists of	Network Scan-to-File Templates ble metadata fields per network of field name, default value and d on user interface for variable o	scan to file templates and unlir l other configurations	nited fields within the template	-
Scan Features	Mixed Size Originals Scan Scan Preview Compression Quality/File ' Original Type (Photo and T Auto Background and Sha Size for Size (for mixed size TWAIN Support / WIA 2.0 Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons	Size Control Text, Photo, Text, Map, Newspa dow Suppression e originals) Support	per / Magazine)		
Scan to Email (Standard)					
Scan Features	Email signatures (6 lines options Scan to Email S/MIME E Email signing (requires S Auto send to self	ncryption	mail message body (user config	urable), email Embedded Web	Server confirmation sheet
Directory Access	Address list via LDAP (Win	dows Active Directory, Exchang	e, Notes, Domino), Device Addı	ress Book	
Scan To (Standard)	<u>'</u>				
Features	Scan to Home Scan to Network (using Se Scan to Email Scan to PC/Server Client (S Scan to Mailbox		gle Drive) ²		
Workflow Scanning (Option					
Scanning Software	Autostore v7 ecopy ShareScan v5.2 eCopy ScanStation v5.2				
Scanning Apps and Xerox App Gallery		Google Drive™, Microsoft® One[ailable in the Xerox App Gallery:	Drive®, Microsoft Office 365™, B xerox.com/AppGallery	ox®, Xerox® Workplace Mobile A	App (iOS/Android)

Security	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170				
eatures	Expanded Authentication Network authentication to	Expanded Authentication Network authentication to access device and/or device services via Kerberos (UNIX / Windows Server 2008), SMB (Windows Server 2008,							
	Windows server 2012), NDS, LDAP authentication								
		- Local Authentication (internal database) - Smart Card authentication – 144k CAC / PIV Card Support (2,048-bit certificate key) / .NET							
	- Secure Data								
	Digitally signed PDF (when Formated and gutbenting								
	Encrypted and authentica Fncrypted / Password-Prot		า เอ Emaii ail and Network Scan Templates	only)					
	- Secure Print (up to 10-digi		•						
	- Immediate Image Overwr	, ,	5 11 5						
	- On-Demand Image Overw - FIPS 140-2 256 bit Hard D		ncludes sanitation of unused are	ea of disk					
	Expanded Authorisation	13K ETICI YPUOTI, 1123, 111 3, 11	111 J, J1 11 , J1 11 10 , J1 11 10 , J1 11 10 , J1 11 10 , J1 11 11 11 11 11 11 11 11 11 11 11 11						
	- SA access based on netwo	ork credentials							
	- Authorisation per user per								
	User Permissions required Secure Network Access	to access Print and Print Fed	atures (e.g. colour access or time	e restrictions) reflects in the print (driver				
	Configuration Watchdog (M	lonitor and remediate 29 se	curity settings):						
	- Front USB Port 2		y y-/-						
	- Rear USB Port 1	- Rear USB Port 1							
		- Rear USB Port 2 - Password Reset Access Control							
		- Password Reset Access Control - 802.1x							
		- Email Alerts - Group 1, 2 and 3 addresses, enablement, Recipient Group Preferences							
	- Hold all jobs								
	- Reprint Saved Jobs	- Reprint Saved Jobs - Scan to Mailbox enablement							
		- Fax Passcode length							
	- System timeout	- System timeout							
	- Show/Hide Login Name								
	- PostScript® Passwords								
	- Remote Services Set-up St	- Remote Services Set-up Supplies / Consumables: Enablement - Remote Services Set-up Supplies / Consumables: Software Download							
		- Remote Services Set-up Supplies / Consumables: Feature Activation							
		- Remote Services Set-up Supplies / Consumables: Update Device Settings							
	· · · · · · · · · · · · · · · · · · ·	- Remote Services Set-up Supplies / Consumables: Daily Synchronisation Time							
		- Remote Services Set-up Supplies / Consumables: Automatically Send Diagnostic Information - FIPS 140-2 Encryption							
	- Firmware Updates (Firmw	are Upgrade) Enable/Disab	le						
	- Scheduled Upgrade								
	- SNMP V1/V2 Protocols: En								
	 Scan services on multifund Remote Start (TWAIN) Sco 		printers						
	- Scan Workflow Managem		· F·····						
	- PII - Conceal Job Names								
	 PII - Show Concealed Job PII - Show Concealed Job 		ing Reports						
	• IP Filter, IPsec, IPv6, TLS v1.		2.1X. SFTP						
	 McAfee[®] Embedded Contro 								
	Port disablement including I	JSB ports							
	Audit LogHide Print Job Names								
	Cisco® Identity Services Eng	jine (ISE) compatible							
	Security Information and Ev	vent Management (SIEM) sı		curity Manager, LogRhythm and !	Splunk ²				
	Full System Common Criteri	a certified by NIAP under H	D Protection Profile for Hardcop	y Devices v1.0 (HCD-PP v1.0) ⁷					
(erox® Integrated RFII Card Reader Optional kit)	Integrated support for most in the multifunction printer pane	, , ,	ding additional security; with em	nbedded multifunction printer car	d readers in				

Fax	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170					
Network Server Fax Features										
Compatibility	TU (CCITT) group 3; Various Xerox Business Innovation Partner Solutions									
Maximum Scan Area	33									
Fax Send Features	Add to Send List (200 numbers	One- or Two-sided Scanning (up to A3) Add to Send List (200 numbers maximum) Build Job, Favourites, Delay Send (specific time) Original Type (photo, text or photo and text)								
Fax Print Features	One- or Two-sided Printing, Sta	iple, Secure Print								
Transmission Resolution	Superfine: 400 x 200 dpi (Scan Fine: 200 x 200 dpi Standard: 200 x 100 dpi	at 600 x 600 dpi)								
Internet Fax Features										
Compatibility		ransmission to remote Internet F cout of documents sent via emai								
Directory Access	Utilises the Unified Address Bo	ok								
Send / Receive	Send: Multi-page TIFF, PDF, PD Receive: TIFF, MTIFF, PDF, PDF									
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-whi	ite)								
Network Protocols	SMTP (send), POP3 (receive)									
Compliance	ITU-T T.37									
Walk-up Fax Features (Optio	nal; Customer-Installable – 1	and 2 lines)								
Compatibility	ITU (CCITT) Group 3									
Speed / Modems	One or Two V.34 modems: 33,	600 bps. Less than 4 seconds pe	r page transmission time							
Compression / Speed	MH/G3, MR/G3, MMR/SG3, JB:	IG/SG3								
Resolution	Walk-up Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: Receive: Accepts all sizes	600 x 600 dpi								
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reducti Page-by-page Job Status at the Delay Start, Build Job, Favourit Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory cap Device Address Book (up to 5,6	e Machine es pacity)								
Fax Receive Features	Output Tray Selection	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password-Protected Mailboxes Secure Receive Receive Timestamp								
Fax forward	Forward to Email or SMB Locat Fax Forward on Receive Only	ion								
Fax Reports	Activity, Dial Directory, Group I Broadcast Report	Directory, Transmission Confirmo	ition, Pending Fax, Options Repo	rt, On Demand Overwrite Report	t, Mailbox Report,					
Directory Access	Utilises the Unified Address Bo Group fax available	ok								
Auto Redial	Up to 14 attempts (per country 1 to 25 minute intervals	y requirements)								
Auto Resend	Up to 5 attempts									

Device Management				
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Configuration Orchestrator, Configuration Watchdog			
Xerox® CentreWαre® Web	A web-based server application for network administrators that permits web browser-based device management from any workstation, whether runnin Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows 7 and Internet Explorer 6.0 and higher. • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote installation			
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install			
Fleet Orchestrator	The Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files and 1-Touch App files.			
Novell NDPS/NEPS	Server gateway application: centralised management tool.			
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. As an SAP customer, you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download.			
Xerox® Device Types for SAP R/3 Intelligent Bar- code Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at office.xerox.com/Software-Solutions			
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at office.xerox.com/Software-Solutions			
Xerox® Embedded Web Serv	Xerox® Embedded Web Server – Integrated Device Web Pages Provided by the Device			
Device Status Job Submission	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN			
	Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)			
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator			
Browsers	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x to 53.x Opera 25.x to 53.x Chrome 48.x to 72.x			
Support	Install print / scan drivers and online support available via support.xerox.com			
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic			
Remote Services				
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for the tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.			
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.			
Accounting Xerox® Standard Accounting	i (Standard)			
Tracking	Copy, Print, Fax, Scan and Email usage			
Accounting	Up to 2,497 User Accounts (User ID)			
ccounting	Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)			
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools. Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry-standard CSV file. 			
Accounting Options – Network Accounting (Allows central server to manage all accounting)				
	 Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at the control panel and pass to a third-party Networking Account Interface with a third-party accounting terminal for accounting user interface 			

Xerox® EX-c C8100 Print Server Powered by Fiery® (Optional)			
Processor	AMD® GX-424CC processor, 2.4 GHz, Quad-Core, 2M cache		
Memory (ESS)	2 GB		
System Disk	500 GB HDD		
Page Description Language	PostScript v 3020		
Features	Fiery Command WorkStation for Mac and Windows Job Preview Job Presets Image Enhance Spool-RIP-Print simultaneously Automatic two-sided printing N-up Watermarks Calibration PANTONE® Colour Enabled Expert Colour Settings: Profile, Rendering and Simulation Fiery FreeForm Create to create personalised files for free Booklet Maker – booklet wizard to create booklets Standard support for long sheet banners Print from USB flash drive Secure Erase Encryption of critical information Secure Printing User authentication Access controls PostScript security Post Docking IP filtering Digitally signed software updates Fiery API Integrates with common cost accounting software, Xerox Standard Accounting, Xerox App Gallery apps and more		
Connectivity	10 Base-T/100 Base-TX/1000 Base-T Ethernet		
Optional	Fiery Options Bundle (Fiery Spot-On, Auto Trapping, Hot Folders, Virtual Printers), Fiery Hot Folders/Virtual Printers, Fiery Spot-On, Fiery Colour Profiler Suite w/EFI ES-2000 Spectrophotometer, Network Switch to connect both printer and Fiery Server to network		

Supplies	Description	Yield		
Toner Cartridge ⁶	Black Cyan Magenta Yellow	59,000 pages 28,000 pages 28,000 pages 28,000 pages		
Transfer Belt Cleaner	1 Assembly	160,000 pages		
Second Bias Transfer Roll	1 Assembly	200,000 pages		
Staple Cartridges	For BR Finisher, Integrated Office Finisher, Office Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge		
	For BR Booklet Maker (1 cartridge per carton)	5,000 each cartridge		
	For Office Finisher Booklet Maker (8 cartridges per carton)	2,000 each cartridge		
Staple Refills	For Integrated Office Finisher, Office Finisher, BR Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill		
Fan Filter	1 Assembly (AltaLink C8170)	500,000 pages		
Xerox® Smart Kit®				
Drum Cartridge ⁸	1 Cartridge per Colour	180,000 pages		
Waste Toner Container w/o Suction Filter ⁹	1 Cartridge (AltaLink C8130/35/45/55)	69,000 pages		
Waste Toner Container with Suction Filter9	1 Cartridge (AltaLink C8170)	69,000 pages		

 $^{^1\,\}text{Maximum}$ volume capacity expected in any one month. Not expected to be sustained on a regular basis. $^2\,\text{Available}$ post-launch via software update.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.



³ Not available in all geographical locations.

⁴ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks. ⁵ Sold separately in some geographical locations.

⁶ Average standard pages. Declared in accordance with ISO/IEC 19798. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes and image quality set-points.

⁷ Under evaluation; certification expected in Q4 2020.

8 Average drum yield is based on a run length of 5 pages of A4 LEF pages, with split of 35% colour / 65% black-and-white pages.

⁹ Waste Toner Container yield will vary depending on type of image, area coverage % and job run length.