





System Specification	WorkCentre 3335	WorkCentre 3345
<b>One-Sided Speed</b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 35 ppm Up to 33 ppm Up to 28 ppm	Up to 42 ppm Up to 40 ppm Up to 34 ppm
<b>Two-Sided Speed</b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 17 ppm Up to 16 ppm Up to 14 ppm	Up to 21 ppm Up to 20 ppm Up to 17 ppm
Monthly Duty Cycle <sup>1</sup>	Up to 50,000 pages / month	Up to 80,000 pages / month
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 4,000 pages	Up to 6,000 pages
Processor	1 GHz	
Memory	1.5 GB	
Connectivity	USB 2.0 10/100/1000Base-T Ethernet Wi-Fi	
Paper Handling	WorkCentre 3335	WorkCentre 3345
Document Feeder		
<b>Capacity</b> <sup>3</sup>	Automatic Document Feeder (ADF): 50 sheets	Reversing Automatic Document Feeder (RADF): 50 sheets
Sizes	Custom Sizes: 5.6 x 5.8 in. to 8.5 x 14 in. / 142 x 148 mm to 216 x 356 mm	I
Weights	16 lb. to 28 lb. bond / 60 to 105 gsm	12.5 lb. to 28 lb. bond / 50 to 105 gsm
Bypass Tray		
<b>Capacity</b> <sup>3</sup>	50 sheets	50 sheets
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm	·
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm	
Media Types	Archive Bond Card Stock Custom Envelopes Heavyweight Labels Lightweight Plain Preprinted Recycled Transparencies	
Τταγ 1	·	
<b>Capacity</b> <sup>3</sup>	250 sheets	
Sizes	Custom Sizes 3.9 x 5.8 in. to 8.5 x 14 in. / 99 x 147 mm to 216 x 356 mm	
Weights	16 lb. bond to 43 lb. bond / 60 to 163 gsm	

Tray 1			
	Archive		
Media Types	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled		
Additional Tray			
Capacity <sup>3</sup>	550 sheets		
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm		
Weights	16 lb. to 43 lb. bond / 60 to 163 gsm		
Media Types	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled		
Total Capacity			
Device Standard Capacity <sup>3</sup>	300 sheets		
Device Total Capacity <sup>3</sup>	850 sheets		
Paper Output			
Output Capacity <sup>3</sup>	150 sheets	150 sheets	
Automatic 2-Sided	Standard		
Device Specification	WorkCentre 3335	WorkCentre 3345	
Electrical Requirements			
North America	110-127 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 7A		
Europe	220-240 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 5A		
Power Consumption			
<b>Operation</b> <sup>4</sup>	Maximum 700 watts		
Standby Mode <sup>4</sup>	Maximum 50 watts		
Power Off Mode <sup>4</sup>	Maximum 0.1 watts		
Sleep Mode <sup>4</sup>	Maximum 3.5 watts		
Warm-up (from Sleep Mode)	As fast as 35 seconds		
Operating Environment			
<b>Required Temperature Range</b> Storage Operating	32°F to 104°F / 0°C to 40°C 50°F to 90°F / 10°C to 32°C		
Required Reletive Humidity	20% to 80%		
<b>Sound Power Levels</b> Operating Standby	55 dB(A) or less 26 dB(A) or less	57 dB(A) or less 26 dB(A) or less	
<b>Sound Pressure Levels</b> Operating Standby	55 dB(A) or less 26 dB(A) or less	57 dB(A) or less 26 dB(A) or less	
Dimensions and Weight (unpackag	ed)		
WorkCentre 3335	Width: 16.3 in. / 414.6 mm Depth: 16.6 in. / 420.6 mm Height: 17.7 in. / 449 mm Weight: 34.19 lb. / 15.51 kg		
WorkCentre 3345	Width: 18.5 in. / 469 mm Depth: 17.5 in. / 444.3 mm Height: 19 in. / 482.6 mm Weight: 38.07 lb. / 17.27 kg		
550-sheet Paper Tray	Width: 14.4 in. / 366 mm Depth: 17.9 in. / 454 mm Height: 5.7 in. / 146 mm Weight: 11.82 lb. / 5.36 kg		

Dimensions and Weight (packa	iged)		
WorkCentre 3335	Width: 21 in. / 533 mm           Depth: 21.6 in. / 549 mm           Height: 23.6 in. / 600 mm           Weight: 46.5 lb. / 19.26 kg		
WorkCentre 3345	Width: 23.1 in. / 588 mm Depth: 21.6 in. / 549 mm Height: 24.6 in. / 626 mm Weight: 47.1 lb. / 21.4 kg		
550-sheet Paper Tray	Width: 22.2 in. / 563 mm Depth: 19.6 in. / 497 mm Height: 11.2 in. / 285 mm Weight: 16.8 lb. / 7.62 kg	Depth: 19.6 in. / 497 mm Height: 11.2 in. / 285 mm	
System Certification/Regulator	y Compliance		
Certifications	FCC Part 15 Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition Section 508 NOM GS Mark EAC ROHS Directive 2011/65/EU WEEE Directive 2011/65/EU WEEE Directive 2012/19/EU Citrix <sup>®</sup> Certified Cerner (undergoing evaluation) Apple <sup>®</sup> AirPrint <sup>®</sup> 1.5 certification Google Cloud Print <sup>®</sup> 2.0 Certification Mopria <sup>®</sup> certified Wi-Fi Alliance Certified Blue Angel MEDITECH ENERGY STAR <sup>®</sup> ECOLOGO <sup>®</sup> EPEAT (United States) To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.		
Сору	WorkCentre 3335	WorkCentre 3345	
Document Scanner	Automatic Document Feeder with 50-sheet capacity	Reversing Automatic Document Feeder with 50-sheet capacity	
Document Scanner Size	Platen: Up to 8.5 x 11.7 in / A4 ADF: 8.5 x 14 in. / 216 x 356 mm	Platen: Up to 8.5 x 11.7 in / A4 RADF: 8.5 x 14 in. / 216 x 356 mm	
Simplex Speed	Up to 30 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	Up to 40 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	
Duplex Speed	Up to 12 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	Up to 8.4 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	
First-Copy-Out Time	As fast as 13 seconds from the Platen		
· · · · · · · · · · · · · · · · · · ·	As lust as 15 seconds from the Flaten		
Sides (input:output)	1:1 and 1:2	1:1, 1:2, 2:2, and 2:1	
		1:1, 1:2, 2:2, and 2:1	
Sides (input:output)	1:1 and 1:2	1:1, 1:2, 2:2, and 2:1	
Sides (input:output) Quantity	1:1 and 1:2 1 to 999	1:1, 1:2, 2:2, and 2:1	
Sides (input:output) Quantity Resolution	1:1 and 1:2         1 to 999         Up to 600 x 600 dpi	1:1, 1:2, 2:2, and 2:1	
Sides (input:output) Quantity Resolution Reduction/Enlargement	1:1 and 1:2         1 to 999         Up to 600 x 600 dpi         Variable zoom from 25% to 400% in 1% increments	1:1, 1:2, 2:2, and 2:1	
Sides (input:output) Quantity Resolution Reduction/Enlargement Concurrency	1:1 and 1:2         1 to 999         Up to 600 x 600 dpi         Variable zoom from 25% to 400% in 1% increments         Concurrent scanning and printing         Automatic Background Suppression Darkness Control ID Card Copy Margin Shift N-up Job Build Photo Mode Programme Ahead Booklet Creation Book Copying with Centre Erase Edge Erase Job Interrupt	1:1, 1:2, 2:2, and 2:1	
Sides (input:output) Quantity Resolution Reduction/Enlargement Concurrency Copy Features	1:1 and 1:2         1 to 999         Up to 600 x 600 dpi         Variable zoom from 25% to 400% in 1% increments         Concurrent scanning and printing         Automatic Background Suppression         Darkness Control         ID Card Copy         Margin Shift         N-up         Job Build         Photo Mode         Programme Ahead         Booklet Creation         Book Copying with Centre Erase         Edge Erase         Job Interrupt         Poster Copying		

Print	WorkCentre 3335	WorkCentre 3345
Page Description Languages	PostScript 3 compatible PCL® 5e, 6 PDF Direct TIFF JPEG	
Maximum Print Area	4 mm from all edges	
Print Features	Watermarks Collation Automatic Two-sided Printing N-up Poster Printing Booklet Print Custom Page Size Fit to Page Scaling Draft Mode Earth Smart Printing Print from USB Job Scheduling Print from Local Drive Save	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL	
Operating Systems	Microsoft® Windows® Vista and later Mac OS <sup>™</sup> 10.8.x and later Various Linux® and Unix distributions	
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® / Airprint® IPv6 Secure FTP Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, SLP <sup>®</sup> v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDN	S, SSDP
Font Capability	136 PostScript fonts 111 scalable PCL fonts 1 Bitmap PCL font	
Mobile Solutions and Mobile Device	Apps	
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox <sup>®</sup> and non Xerox <sup>®</sup> devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox <sup>®</sup> and non Xerox <sup>®</sup> devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print <sup>™</sup>	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook notebook computers and any other web-connected device. <sup>6</sup>	
Xerox <sup>®</sup> Print Service Plug-in for An- droid <sup>™</sup> (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers.You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play <sup>™</sup> store.	
Scan	WorkCentre 3335	WorkCentre 3345
Capability	Colour and Black-and-white	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is tra	ansferring scan to network or fax jobs
Input Speed - Black and White	Scan up to 20 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	Scan up to 24 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm
Input Speed - Colour	Scan up to 6 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	Scan up to 8 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm
Resolution	Black and White: Optical – 600 x 600 dpi Enhanced up to 4800 x 4800 dpi	
Bit Depth	8-bit Greyscale	
Maximum Scan Area	Platen: Up to 8.5 x 11 in. / A4 Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm	

Scan	WorkCentre 3335	WorkCentre 3345
Network Filing Protocol	FTP	
Network ming Protocol	SMB/SMB2 SMTP/POP3	
File Formats	PDF Single-page and Multi-page TIFF JPEG BMP	
Scan Driver Compatibility	WIA TWAIN	
Supported Scan Destinations	Scan to Email (SMTP/POP3) Scan to WSD Scan to Application (TWAIN Network) Scan to WSD (WSD Scan) Scan to Mac 10.9 or later (Network/Mac ICA) Scan to USB Scan to Network Computer (SMB/FTP) Scan to Folder	
Security	WorkCentre 3335	WorkCentre 3345
Security Features	802.1x Secure HTTPS (SSL/TLS) Secure IPP Secure Print SSL IP Filtering IPv6 SNMP v3 WEP (64-/128-bit) WPA2-PSK (AES) WPA / WPA2-Personal WPA / WPA2-Enterprise Network Address Book Authentication (LDAP, Windows Kerberos)	
WiFi Security		
	Authentication Method Open WPA PSK WPA PSK / WPA2 PSK WPA Enterprise WPA Enterprise / WPA2 <sup>™</sup> Enterprise WPA Enterprise Authentication Method options: • PEAPVO MS-CHAPV2 • EAP-TLS • EAP-TLS PAP • EAP-TTLS CHAP	Encryption WEP 64 / 128-bit ASCII / HEX TKIP AES TKIP AES
Fax'	WorkCentre 3335	WorkCentre 3345
Fax Speed	33 Kbps	
Memory	· ·	50 MB
Resolution	5 MB 50 MB Up to 300 x 300 dpi (Super-Fine/Photo) resolution Up to 203 x 196 dpi (Fine) resolution Up to 203 x 98 dpi (Standard) resolution	
Compression	MH/MR/JBIG/JPEG	
Fax Features	Address Book (Up to 200 speed dials, 209 group dials) Auto Redial Auto Reduction Colour Fax Send Delayed Send Fax Forward to Email/Fax Junk fax Protection Memory Receive PC Fax (Windows only) Secure Fax	
Device Management		
Xerox <sup>®</sup> CentreWare <sup>®</sup> Web		
Device Status	Web server embedded • Tray status/contents • Consumables status	
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete	
Job Submission	Print-ready files (PS, PCL®5c/6, PDF, TIFF Output feature selection	

Device Management			
Xerox <sup>®</sup> CentreWare <sup>®</sup> Web			
Device Administration	Allows simple, remote installation setting of configuration options and management of the device.		
Browsers	Microsoft <sup>®</sup> Internet Explorer 6, 7 Firefox <sup>®</sup> 2,, 3 Safari <sup>®</sup> 3.0		
Xerox <sup>®</sup> CentreWare <sup>®</sup> Internet Service	es – Integrated Device Web Page		
	<ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> </ul>		
Xerox® Standard Accounting (Stand	ard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 1,000 User accounts (User ID) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)		
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file.</li> </ul>		
Remote Print Services			
Xerox <sup>®</sup> MeterAssistant <sup>®</sup> Service	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox <sup>®</sup> device usage. Eliminates the need for time-consumin- gend-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox <sup>®</sup> SuppliesAssistant <sup>®</sup> Service	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox®, allowing for problems to be solved faster with increased uptime.		
What's In The Box			
	<ul> <li>WorkCentre 3335 Multifunction Printer or WorkCentre 3345 Multifunction Printer</li> <li>Standard Capacity Print cartridge: 2,600 pages<sup>8</sup></li> <li>Software and Documentation CD (with Safety, Regulatory, Recycling and Disposal Guides), Print Drivers and Warranty Statement</li> <li>Installation Guide</li> <li>Quick Use Guides</li> <li>Power cord</li> <li>Fax cord</li> </ul>		
Supplies and Accessories	Quantity	Part Number	
Supplies			
Extra-High Capacity Print Cartridges	15,000 standard pages <sup>8</sup>	106R03623	
High Capacity Print Cartridges	8,500 standard pages <sup>8</sup>	106R03621	
Drum Cartridge	30,000 standard pages <sup>9</sup>	101R00555	
Accessories			
550-sheet Paper Tray		097N02254	
Near Field Communication (NFC) Enablement Kit		097N02255	
WorkCentre 3335/3345 Card Reader Enablement Kit (without card reader)       497K17990			

<sup>1</sup>Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks. <sup>6</sup> Power states defined per ENERGY STAR<sup>®</sup> Programme requirements for Imaging Equipment.

<sup>5</sup> Printing from USB. <sup>6</sup> Depending on the specific mobile device, versions or vendor, the mobile device may require a free download of the app from the appropriate store(s).

Requires analogue phone line. \*Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

<sup>9</sup> Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.



©2016 Xerox Corporation. All rights reserved. Xerox<sup>®</sup>, Xerox and Design<sup>®</sup>, CentreWare<sup>®</sup>, Global Print Driver<sup>®</sup>, MeterAssistant<sup>®</sup>, Mobile Express Driver<sup>®</sup>, SuppliesAssistant<sup>®</sup>, and WorkCentre<sup>®</sup> are trademarks of Xerox Corporation in the United States and/or other countries. Mopria is a trademark of the Mopria Alliance. As an ENERGY STAR<sup>®</sup> and thousand a set calculation of record polation in the office states along a state states are calculated in the most of the most of the most of the most of the the states are registered U.S. marks. The information in this brochure is subject to change without notice. 12/16 BR19338 333SS-021D