

Xerox[®] WorkCentre[™] 6655 Colour Multifunction Printer

The WorkCentre 6655 Color Multifunction Printer is built on Xerox[®] ConnectKey[®] Technology. For more information, go to **www.connectkey.com**.



System Specifications	WorkCentre 6655/X	
Speed (Colour and Black and White)	Up to 36 ppm 8.5 x 11 in. Up to 35 ppm A4 / 210 x 297 mm Up to 29 ppm 8.5 x 14 in. / 216 x 356 mm	
Monthly Duty Cycle ¹	Up to 100,000 pages	
Recommended Average Monthly Print Volume ²	Up to 10,000 pages	
Hard Drive / Processor / Memory	Minimum 250 GB / 1 GHz Dual-core / 4 GB	
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0, Optional Wi-Fi (with Xerox® Wireless Networking Adapter)	
Controller Features	Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning	
Copy and Print		
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 2400 x 600 dpi	
First-print-out Time	As fast as 11 seconds colour / 11 seconds black and white	
First-copy-out Time	As fast as 16 seconds colour / 15 seconds black and white	
Page Description Languages	Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®)	
Print Features	Print from USB, Earth Smart Driver Settings, Store and Recall Driver Settings, Bidirectional Status, Smart Duplex, Automatic Two-sided, Booklet Printing, Proof Print, N-up, Print Around	
Mobile Printing	Apple® AirPrint, Xerox® PrintBack, Xerox® Mobile Print Solution (Optional), Xerox® Mobile Print Cloud (Optional), Mopria™ certified	
Scan		
Standard Features	Destinations: Scan to Mailbox, Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-page PDF/XPS/TIFF, Encrypted / Password Protected PDF, Linearised PDF / PDF/A	
Optional Features	Software Packages: ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® Professional, numerous solutions available through various Xerox Alliance Partners	
Fax		
Standard Features	Embedded Fax ³ , LAN Fax, Internet Fax, Server Fax	
Security		
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408) (undergoing evaluation), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions	
Optional Features	McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET)	
Accounting		
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement	
Optional Features	Equitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Alliance Partners	

Calend Para Design and Tayle hore-stands frach hore. Status and Tayle hore status and the set fractional stat	Device Specifications					
Damb. Lease. Juit Cost. Justic Lease. Justic Lease. Justic Lease. Justic Cost. Justic Lease. Justic Cost. Justic Lease. Justic Cost. Justic Cost		US English, International English, Int	ernational French, Italian, Germai	n, International Spanish, Dutch, Brazi	lian Portuguese, Swedish, Norwegian,	
openal AccessoriesSSS also there Frider Series Accessories ID Systems is intermediation of the System is a series o						
and seriesSince SeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeriesSeries						
Decisical Requirements Visitage 110.127 VAC u/. 10% Frequent/S-204014 Le/ 3/3, 10 A Surge of Mage 110.127 VAC u/. 10% Frequent/S-204014 Le/ 3/3, 10 A Image 100.100 Set 100.100.100 Set 100.100 Set 100.100 Set 100.100.100 Set 1	Optional Accessories	Stand Smart Card Enablement Kit Xerox Secure Access Unified ID Syste Xerox® Wireless Networking Adapter	Stand Smart Card Enablement Kit Xerox Secure Access Unified ID System® Xerox® Wireless Networking Adapter			
imageRespire y 5000 He / 3 33, Yo ABrone y 5000 He / 3 33, Yo ASolution IPresency 5000 He / 3 2007 Solution ISolution ISolution ISolution IPresence 5000 ModeSolution ISolution ISolution IPresence 5000 ModeSolution ISolution ISolution IPresence 5000 ModeSolution ISolution ISolution ISolution ISolution ISolution ISolution ISolution ISolution ISolution IISolution IISolution III IISolution III III IIISolution III III III III IIII III IIII IIII I	Electrical Requirements					
New ConstructionRegion (2006) 2007 - 2006 (2007)Source Colspan="2">Source Co	North America					
Printing 100% 56.84 km/ls Standby Mode 120% 7.10.44 km/ls Standby Mode 220% 7.10.44 km/ls Power Sove Mode 220% 7.10.44 km/ls 220% 27.10.44 km/ls 220% 7.10.44 km/ls Power Sove Mode 200% 7.10.44 km/ls Operating Environment 200% 271 km/ls Required Relative Humidity 15% Is 85% Sound Power Levels Operating 51.8 dB(A). Standby A1.4 B(A) Sound Power Levels Operating 51.8 dB(A). Standby A1.4 B(A) Sound Power Levels Operating 51.8 dB(A). Standby A1.4 B(A) Sound Power Levels Operating 51.8 dB(A). Standby A1.4 B(A) Sound Power Levels Operating 51.8 dB(A). Standby A1.4 B(A) Sound Power Levels 21.2 In. / 58.8 m/l Sound Power Levels 21.4 In. / 68.1 m/l Operating STM (Marin 21.8 In. / 55.9 m/l Sound Cereet Evels 29.1 n. / 73.7 mm Sound Cereet Evels 29.1 n. / 73.7 mm Sound Cereet SSTX 26.6 in. / 67.7 mm Sound Cereet SSTX 26.6 in. / 67.7 mm Sound Cereet Sound	Europe	5	Voltage : 220-240 VAC +/- 10 %			
of with a stand in the second of the seco	Power Consumption					
Top we have been been been been been been been be	Printing					
302-27 wataQeneration of the Signet Sector Secto	Standby Mode					
Required Temperature Range 41°10 °00° F (5°16 32°C () Required Relative Humidity 15% to 55% Sound Power Levels Operating 5.76 B(A), Standhy 6.14 U-U-U-U-U-U-U-U-U-U-U-U-U-U-U-U-U-U-U-	Power Save Mode					
Required Relative Humidity 15% to 85%. Sound Pressure Levels Operating: 51.8 dB(A). Standby: 25.1 dB(A) Dimensions and Weight (Unpackaged) With Depth Height Weight WorkCentre 6655X 21.2 in. / 53.8 mm 21.8 in. / 553 mm 24.6 in. / 625 mm 82.9 lbs. / 37.6 kg Sound Pressure Level 19.2 in. / 488 mm 19.2 in. / 488 mm 9.7 lbs. / 4.6 kg Stand 29 in. / 737 mm 25.5 in. / 699 mm 13.1 in. / 332 mm 28.4 lbs. / 12.9 kg Dimensions and Weight (Unpackaged) Width Depth Height Weight Dimensions and Weight (Deckaged) Width Depth Height Weight Stand 29.1 in. / 500 mm 20.5 in. / 590 mm 9.6 in. / 751 mm 9.6 lbs. / 43.9 kg Stand 29.1 in. / 500 mm 20.9 in. / 500 mm 9.4 in. / 209 mm 13.5 lbs. / 6.2 kg Certifications FCC Prot 15. Closs A FCC Prot 5.6 Gos O for CPC Prot 0.5 Gos O for CPC Prot 0.5 Close A FCC Prot 16.6 Gos O for CPC Prot 0.5 Close A FCC Prot 16.6 Gos O for CPC Prot 0.5 Close A FCC Prot 16.6 Gos O for CPC Prot 0.5 Close A FCC Prot 16.6 Gos O for CPC Prot 0.5 Close A FCC Prot 16.5 Close A FCC Prot 16.5 Close A FCC Prot 16.5 Close A FCC Prot 16.5 Close A FCC Prot 15.2 FCOS O for Clo	Operating Environment					
Sound Power Levels Operating 576 B(A), Standby: 23.1 B(A) Sound Pressure Levels Operating: 51.8 dB(A), Standby: 23.1 B(A) Dimensions and Weight Width Depth Height Weight Unpackaged) Virtic Stand Pressure Levels Virtic	Required Temperature Range	41° to 90° F (5° to 32° C)				
Cond Presure Levels Operating 51.8 dB(A), Standary, 25.1 dB(A) Dimensions and Weight With Depth Height Weight WorkCentre 6655/X 21.2 in, / 538 mm 21.8 in, / 553 mm 24.6 in, / 625 mm 82.9 lbs, / 37.6 kg Stond Presure Levels 19.2 in, / 488 mm 19.2 in, / 488 mm 55. m, / 138 mm 9.7 bs, / 4.4 kg Stond 29 in, / 737 mm 27.5 in, / 699 mm 13.1 in, / 320 mm 28.4 lbs, / 12.9 lg Dimensions and Weight (Packaged) With Depth Height Weight WorkCentre 6655/X 26.4 in, / 671 mm 26.6 in, / 675 mm 29.6 in, / 751 mm 9.6 8 lbs, / 43.9 lg Stond 23.9 in, / 607 mm 23.5 in, / 580 mm 10.6 in, / 270 mm 3.7 lbs, / 62. kg Stand 22.1 in, 560 mm 20.9 in, / 530 mm 10.6 in, / 270 mm 3.6 lbs, / 16.6 lg Certifications CC Pent 15, Class A CC Pent 15, Class A CC Pent 68	Required Relative Humidity	15% to 85%				
Dimensions and Weight (Unpackaged) With With Depth Height Height Weight Weight (Unpackaged) WorkCentre 6655/X 21.2 nr. / 538 mm 21.8 in. / 553 mm 24.6 in. / 625 mm 62.9 lbs. / 37.6 lpg Stand 29 in. / 737 mm 27.5 in. / 699 mm 13.1 in. / 332 mm 28.4 lbs. / 12.9 lpg Dimensions and Weight (ackaged) With Depth Height Weight WorkCentre 6655/X 26.4 in. / 671 mm 26.6 in. / 675 mm 29.6 in. / 751 mm 9.6 8 lbs. / 43.9 lg Stand 23.9 n. / 607 mm 23.9 in. / 500 mm 20.9 in. / 500 mm 13.1 lb. / 332 mm 13.7 lbs. / 62.kg Stand 23.9 n. / 607 mm 29.6 in. / 507 nm 29.6 in. / 720 mm 36.6 lbs. / 16.6 lg Certifications FCC Port 15. Class A CCC Port 56 CC Port 15. Class A CC Port 15. Class A Co Contro Clarenci (IEEE 2002 standed Lindergoing evolucion) CLass B EAC and White Up to 54 inoges per minut	Sound Power Levels	Operating 6.76 B(A), Standby: 4.14 B	3(A)			
(Unpackaged)Image: Control of SignmImage: Sign of SignmImage: Signm	Sound Pressure Levels	Operating: 51.8 dB(A), Standby: 25.1	dB(A)			
Solvenet Feeder 19.2 in. / 488 mm 5.5 in. / 138 mm 9.7 ibs. / 4.4 kg Stand 29 in. / 737 mm 27.5 in. / 699 mm 13.1 in. / 332 mm 28.4 lbs. / 12.9 kg Dimensions and Weight (Gackaged) Width Depth Height Weight WorkCentre 6655/X 26.4 in. / 671 mm 26.6 in. / 675 mm 29.6 in. / 751 mm 96.8 lbs. / 43.9 kg SSosheet Feeder 23.9 in. / 607 mm 23.5 in. / 596 mm 9.4 in. / 239 mm 13.7 lbs. / 62.4 kg Stand 20.9 in. / 500 mm 20.9 in. / 530 mm 10.6 in. / 270 mm 36.6 lbs. / 16.6 kg Certifications CC Part 15, Class A FCC Part 68 CC Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/C5A 60950-1/07, 2nd Editor EAC Common Criteria (IEEE 2500.2 standard (undergoing evaluation)) NOM Usariane Sinter Vertified To an evaluation of the form of	-	Width	Depth	Height	Weight	
Stand29 In. / 737 mm27.5 in. / 699 mm13.1 in. / 332 mm28.4 lbs. / 12.9 kgDimensions and Weight (Packaged)WidthDepthHeightWeightWorkCentre 6655/X26.4 in. / 671 mm26.6 in. / 675 mm29.6 in. / 751 mm96.8 lbs. / 43.9 kgSolvhet Feder23.9 in. / 607 mm23.5 in. / 596 mm9.4 in. / 239 mm13.7 lbs. / 62. kgStand22 in. / 560 mm20.9 in. / 530 mm10.6 in. / 270 mm36.6 lbs. / 16.6 kgCertificationsFCC Part 15. Closs A FCC Part 68 CE Mark applicable to Directives 2006/95/FC 2004/108/FC and 1999/5/FC UIL 60950-1707. 2nd Edition EAC WEEE Directive 2002/96/FC and FDA/CDB/FL Cook 1 1099/5/FC UIL 60950-1707. 2nd Edition EAC WEEE Directive 2002/96/FC and FDA/CDB/FL Cook 1 Laser Product CE mark applicable Directive 2011/65/FC (RoHS) Common Citteria (IEEE 2600.2 standard (undergoing evaluation)) NOM UKaine Blue Angel (undergoing evaluation) ECOLGOG ⁶ (undergoing evaluation) EPAT (United States) (undergoing evaluation) EPAT (United States) (undergoing evaluation) Citrix EPAT (United States) (undergoing evaluation) Citrix ENERCY STAP qualified Up to 54 intoges per minute (ipm) Letter /51 ipm A4 (simplex) Up to 25 ipm letter /28 ipm A4 (simplex) Up to 14 ipm letter /31 ipm A4 (simplex)Weifers to to to 53 tb. hoord to 32 lb. boord to 32 lb. boord to 32 lb. boord to 32 lb. boord to 32 bb. boord to 25 spm to 125 spm to 125 spm </td <th>WorkCentre 6655/X</th> <td>21.2 in. / 538 mm</td> <td>21.8 in. / 553 mm</td> <td>24.6 in. / 625 mm</td> <td>82.9 lbs. / 37.6 kg</td>	WorkCentre 6655/X	21.2 in. / 538 mm	21.8 in. / 553 mm	24.6 in. / 625 mm	82.9 lbs. / 37.6 kg	
Dimensions and Weight (Packaged)With WithDepthHeightWeightWorkCentre 6655/X26.4 in. / 671 mm26.6 in. / 675 mm9.6 in. / 751 mm96.8 lbs. / 43.9 kgStosheet Feeder23.9 in. / 600 mm23.5 in. / 596 mm9.4 in. / 239 mm13.7 lbs. / 62.8 gStand2 lin. / 500 mm20.9 in. / 530 mm10.6 in. / 270 mm36.6 lbs. / 16.6 kgCertificationsFCC Part 15. Closs A FCC Part 68 CE Mark applicable to Directives 2006/95/EC 2004/108/EC and 1999/5/EC UI 60950-1/CSA 60950-1.07. 2nd Edition EAC.Stand 10.9 m/ 500	550-sheet Feeder	19.2 in. / 488 mm	19.2 in. / 488 mm	5.5 in. / 138 mm	9.7 lbs. / 4.4 kg	
(Package)Image: Control of the second se	Stand	29 in. / 737 mm	27.5 in. / 699 mm	13.1 in. / 332 mm	28.4 lbs. / 12.9 kg	
Sol-sheet Feeder23.9 in./ 607 mm23.5 in./ 596 mm9.4 in./ 239 mm13.7 lbs./ 6.2 kgStand22 in./ 560 mm20.9 in./ 530 mm10.6 in./ 270 mm36.6 lbs./ 16.6 kgCertificationsCP cont 15, Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC, UL 60950-1/C3. A do950-1-07, 2nd Edition EAC WEEE Directive 2002/96/EC and FDA/CDRH-Class 1 Laser Product CE mark applicable in Directives 2016/95/EC, 2004/108/EC and 1999/5/EC, UL 60950-1/C3. A do950-1-07, 2nd Edition EAC WEEE Directive 2002/96/EC and FDA/CDRH-Class 1 Laser Product CE mark applicable Directives 2016/95/EC, (RoHS) Common Criteria (IEEE 2600.2 standard (undergoing evaluation)) NOM Ukraine Bue Angel (undergoing evaluation) ECOLOGO ⁶ (undergoing evaluation) ECOLOGO ⁶ (undergoing evaluation) ECOLOGO ⁶ (undergoing evaluation) Citir ENEGY STAR® qualified To view the latest list of certifications, go to www.xerox.com/OfficeCertification EVELOGO ⁶ (undergoing evaluation) Citir ENEGY STAR® qualified To view the latest list of certifications, go to www.xerox.com/OfficeCertification EVELOG Stare 1 up to 54 images per minute (pm) Leter / 51 ipm A4 (simplex) Up to 25 ipm Letter / 24 ipm A4 (simplex) Up to 25 ipm Letter / 24 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm		Width	Depth	Height	Weight	
Stand20 ln./ 500 mm10.6 in./ 270 mm36.6 lbs./ 16.6 kgCertificationsCC Part 15, Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition EAC WEEE Directive 2002/96/EC and FDA/CDRH-Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoHS) Common Citeria (IEEE 2600.2 tand FDA/CDRH-Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoHS) Common Citeria (IEEE 2600.2 tand FDA/CDRH-Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoHS) Common Citeria (IEEE 2600.2 tand FDA/CDRH-Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoHS) Common Citeria (IEEE 2600.2 tand FDA/CDRH-Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoHS) Common Citeria (IEEE 2600.2 tand FDA/CDRH-Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoHS) Common Citeria (IEEE 2600.2 tand FDA/CDRH-Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoHS) Common Citeria (IEEE 2600.2 tand FDA/CDRH-Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoHS) Common Citeria (IEEE 2600.2 tand FDA/CDRH-Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoHS) Common Citeria (IEEE 2600.2 tand so tand so tand so tand tand tand tand tand tand tand tand	WorkCentre 6655/X	26.4 in. / 671 mm	26.6 in. / 675 mm	29.6 in. / 751 mm	96.8 lbs. / 43.9 kg	
Certifications FCC Part 15, Class A FCC Part 68 FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1-07, 2nd Edition EAC WEEE Directive 2002/96/EC and FDA/CDRH-Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoH5) Common Criteria (IEEE 2600.2 standard (undergoing evaluation)) NOM Ukraine Blue Angel (undergoing evaluation) ECOLOGO® (undergoing evaluation) ECOLOGO® (undergoing evaluation) ECOLOGO® (undergoing evaluation) ECOLOGO® (undergoing evaluation) ECOLOGO® (undergoing evaluation) Citrix ENERCY STAR® qualified To view the latest list of certifications, go to www.xerox.com/OfficeCertifications. Paper Handling Duplex Automatic Document Feed=/// DADF Capacity ⁴ 60 sheets Speed Bluck and white Up to 54 images per minute (ipm) Letter / 51 ipm A4 (simplex) Up to 25 ipm Letter / 24 ipm A4 (duplex) Up to 25 ipm Letter / 24 ipm A4 (duplex) Up to 29 ipm Letter / 24 ipm A4 (duplex) Out to 29 ipm Letter / 24 ipm A4 (duplex) Paper Sizes Sensed 5.5 x 5.5 in. to 8.5 x 14 in./ 139.7 x 139.7 mm to 216 x 356 mm Weights Simplex: 13 lb	550-sheet Feeder	23.9 in. / 607 mm	23.5 in. / 596 mm	9.4 in. / 239 mm	13.7 lbs. / 6.2 kg	
FCC Part 15, Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition EAC WEEE Directive 2002/96/EC and FDA/CDRH-Class 1 Laser Product CE mark applicable Directives 2011/65/EC (RoHS) Common Citteria (IEEE 2600.2 standard (undergoing evaluation)) NOM Ukraine Blue Angel (undergoing evaluation) ECOGO® (undergoing evaluation) ECDGO® (undergoing evaluation) EVEREV STAR® qualified To view the latest list of certifications, go to www.xerox.com/OfficeCertifications. Paper Handling Duplex Automatic Document Fee-VDFJ Capacity' 60 sheets Speed Black and white Up to 54 images per minute (pm) Letter / 51 ipm A4 (simplex) Up to 25 ipm Letter / 24 ipm A4 (duplex) Up to 25 ipm Letter / 24 ipm A4 (duplex) Up to 25 ipm Letter / 24 ipm A4 (duplex) Up to 25 ipm Letter / 24 ipm A4 (duplex) Paper Sizes Sensed 5.5 x.5 .5 .in. to 8.5 x 14 in. / 139.7 xm to 216 x 356 mm Weights Simplex. 13 lb. bond to 32 lb. bond / 50 gsm to 125 gsm	Stand	22 in. / 560 mm	20.9 in. / 530 mm	10.6 in. / 270 mm	36.6 lbs. / 16.6 kg	
Duplex Automatic Document Feed// (DADF) Capacity' 60 sheets Speed Up to 54 images per minute (ipm) Letter / 51 ipm A4 (simplex) Up to 25 ipm Letter / 24 ipm A4 (duplex) Colour Up to 29 ipm Letter / 28 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (duplex) Paper Sizes Sensed 5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mm Weights Simplex: 13 lb. bond to 32 lb. bond / 50 gsm to 125 gsm		FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition EAC WEEE Directive 2002/96/EC and FDA/CDRH–Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoHS) Common Criteria (IEEE 2600.2 standard (undergoing evaluation)) NOM Ukraine Blue Angel (undergoing evaluation) ECOLOGO® (undergoing evaluation) ECOLOGO® (undergoing evaluation) EPEAT (United States) (undergoing evaluation) Citrix ENERGY STAR® qualified				
Capacity ⁴ 60 sheetsSpeed Black and whiteUp to 54 images per minute (ipm) Letter / 51 ipm A4 (simplex) Up to 25 ipm Letter / 24 ipm A4 (duplex)ColourUp to 29 ipm Letter / 28 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (duplex)Paper Sizes Sensed5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mmWeightsSimplex: 13 lb. bond to 32 lb. bond / 50 gsm to 125 gsm						
Speed Up to 54 images per minute (ipm) Letter / 51 ipm A4 (simplex) Black and white Up to 55 ipm Letter / 24 ipm A4 (duplex) Colour Up to 29 ipm Letter / 28 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (duplex) Paper Sizes Sensed 5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mm Weights Simplex: 13 lb. bond to 32 lb. bond / 50 gsm to 125 gsm	•					
Black and white Up to 54 images per minute (ipm) Letter / 51 ipm A4 (simplex) Colour Up to 25 ipm Letter / 24 ipm A4 (duplex) Up to 29 ipm Letter / 28 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (duplex) Paper Sizes Sensed 5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mm Weights Simplex: 13 lb. bond to 32 lb. bond / 50 gsm to 125 gsm						
Paper Sizes Sensed 5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mm Weights Simplex: 13 lb. bond to 32 lb. bond / 50 gsm to 125 gsm	Black and white	Up to 25 ipm Letter / 24 ipm A4 (duplex) Up to 29 ipm Letter / 28 ipm A4 (simplex)				
Weights Simplex: 13 lb. bond to 32 lb. bond / 50 gsm to 125 gsm	Paper Sizes Sensed					
	Weights	Simplex: 13 lb. bond to 32 lb. bond / 50 gsm to 125 gsm Duplex: 16 lb. bond to 32 lb. bond / 60 gsm to 125 gsm				

Pupper Trav	
Bypass Tray	150 sheets
Capacity ⁴	
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 356 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm
Types	Plain Punched Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Glossy Cardstock Glossy Cardstock Recycled Bond Labels Pre-printed Envelopes Custom
Trays 1	
Capacity ⁴	550 sheets
Sizes	Custom Sizes from 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm
Types	Plain Punched Letterhead Lightweight Cardstock Cardstock Recycled Bond Labels Pre-printed Custom
1 Additional Tray	
Capacity ⁴	550 sheets
Sizes	Custom Sizes from 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm
Types	Plain Punched Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Glossy Cardstock (simplex only) Cardstock (simplex only) Recycled Bond Labels Pre-printed Custom
Total Capacity	
Device Standard Capacity ⁴	700 sheets
Device Total Capacity	1,250 sheets
Paper Output	
Capacity	250 sheets face down with tray full sensor
Offline Convenience Stapler	
Capacity ⁴	20-sheet stapling, single position
Сору	
Speed (Colour and Black and White)	Up to 36 ppm 8.5 x 11 in. Up to 35 ppm A4 / 210 x 297 mm Up to 29 ppm 8.5 x 14 in. / 216 x 356 mm
First-copy-out Time	As fast as 16 seconds colour / 15 seconds black and white
Sides (input:output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max.)	Up to 600 x 600 dpi
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments

Copy Features	Annotation and Bates [™] stamping (with colour capability and font size adjustment) Authertication for Services Auto Paper Select Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stabling	
Xerox [®] Copier Assistant [®]	Stepsing Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com	
Print		
First-print-out Time	As fast as 11 seconds colour / 11 seconds black and white	
Print Resolution	Up to 2400 x 600 dpi	
Print Features	Application DefaultsBanner Sheet Enable / DisableBidirectional StatusBooklet PrintingCover SelectionDelay Print (specific time)User PermissionsImage Options (Toner Saver, Standard and High ResolutionJob Identification (Print ID or Banner, Print ID in margins on first page only or all pages)LAN Fax (requires optional Fax Kit)Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size)OverlaysPaper Selection by AttributePrint AroundProof PrintSample SetSaved JobSecure Print with Timed DeletionSpecial Pages (exception page programming: covers, inserts, exception pages)Store and Recall Driver SettingsSustainability Features (Xerox* Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL	
Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Ubundwe 8.1 (32- and 64-bit) Ubundwe 8.1 (32- and 64-bit) Ubundwe 13.10 x64 openSUSE® 13.1 x64	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Apple® Bonjour® IPv6 Secure FTP	
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP [®] v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP	
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	

Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	
Print Solutions		
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.	
Xerox® Mobile Print Solution (Optional)	Xerox [®] Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox [®] Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.	
Unified Address Book for Fax, Inter	net Fax, Email and Scan to	
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc.	
Scan		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)	
Speed Black and white	Up to 54 images per minute (ipm) Letter / 51 ipm A4 (simplex) Up to 25 ipm Letter / 24 ipm A4 (duplex)	
Colour	Up to 29 ipm Letter / 28 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (duplex)	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)	
Maximum Scan Area	Up to 8.5 x 14 in. / 216 x 356 mm	
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options	
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS	
File Compression	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression–single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Encrypted / Password Protected PDF (Network Scan Templates only) Linearised PDF, PDF/A	
Document Management Fields (Meta Data)	 Features only available in Network Scan to File Templates: 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations Customised fields viewed on user interface for variable data input 	
Scan Features	Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression TWAIN Support, WIA Support Bound Originals Edge Erase Reduction / Enlargement Single Touch Scan buttons (up to 10)	
Scan to Email (Standard)		
Scan Features	 Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self 	
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)	
Scan to (Standard)		

Network Scanning – Software Solu	utions		
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organisation tools: • PaperPort Professional image viewing and file management software – Complete PDF functionality – Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability		
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® multifunction printer, you can route documents directly into the precise document repository folder, just like you would from your PC. At the multifunction printer, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.		
Xerox® ConnectKey Share to Cloud (Optional)	Xerox [®] ConnectKey Share to Cloud provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox [®] multifunction printer to popular cloud services and email, such as Google Docs [™] , SalesForce.com, Office 365 and Dropbox [™] and gives employees anytime, anywhere access to their most important documents using mobile devices.		
Xerox® ConnectKey for DocuShare® (Optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer.		
Security			
Features	 Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), SMB Windows Server 2003 / Windows Server 2008), NDS, LDAP Xerox Secure Access Unified ID System[®] Local Authentication (internal database) Smart Card authentication - 144k CAC / PIV Card Support (2048 bit certificate key) / .NET Secure Data Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted / Password Protected PDF (when using Email and Network Scan Templates only) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorisation SA access based on network credentials Authorisation per user per service User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, SL v3.0, SNMPv3, HTTPS, 802.1X, Cisco® TrustSec Identity Services Engine integration, Device Security McAfee Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, , McAfee Integrity Control (optional) Common Criteria Certification ISO 15408 (undergoing evaluation) Xerox Secure Access Unified ID System integrates your Xerox® multifuncti		
	any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions		
Fax			
Embedded Fax ³ , LAN Fax, Internet	t Fax, Server Fax		
Fax Speed	Up to 33.6 Kbps (analog)		
Memory	Uses device memory		
Resolution	Up to 600 x 600 dpi (Super Fine) resolution Up to 200 x 200 dpi (Fine) resolution Up to 200 x 100 dpi (Standard) resolution		
Compression	MH, MR, MMR, JBIG		
Fax Features	Duplex Scanning Reports Auto Redial Auto Reduction Cover Page Delayed Send Fax Forward to Email Memory Receive Polling Secure Fax Speed Dials (up to 200 individual, 100 group)		

Device Management			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP		
manugement support	MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2		
Xerox® CentreWare® Web	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asse management. Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. CentreWare Integration available for Tivoli[®] NetView[®], Unicentre TNG[®], Microsoft Management Console (MMC), HP[®] OpenView[®] 		
Novell NDPS/NEPS	Server gateway application: centralised management tool.		
Xerox® Device Manager	 Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: Device monitoring and troubleshooting Extensive reporting and discovery of new devices Usage collection, chargeback and billing capabilities 		
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. www.office.xerox.com/software-solutions		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions		
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions		
CentreWare Internet Services – Int	tegrated Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel		
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12		
Support	Install print / scan drivers and online support available via web page		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese		
Remote Services			
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time- consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox [®] SuppliesAssistant [®]	Automatically orders supplies for Xerox [®] output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.		
Accounting			
Xerox® Standard Accounting (Stan	dard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)		
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file 		
Accounting Options – Network Acc	counting – Third Party Enablement		
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface 		

What Comes in the Box				
	 WorkCentre 6655 Colour Multifunction Printer Starter Toner Cartridges – One of each (Cyan, Magenta, Yellow: 3,000 print capacity⁵; Black: 6,000 print capacity⁵) Quick Installation Guide, Product Information Guide, Driver CD, Documentation CD (User Manual, System Admin Guide) Power Cable Fax Cord 			
Supplies and Accessories	Description	Quantity	Part Number	
Supplies	Black Toner Cartridge	12,000 std. pages⁵	106R02755	
	Cyan Toner Cartridge	7,500 std. pages⁵	106R02752	
	Magenta Toner Cartridge	7,500 std. pages⁵	106R02753	
	Yellow Toner Cartridge	7,500 std. pages⁵	106R02754	
	Staple Cartridge	3,000 staples	108R00823	
Routine Maintenance Items	Imaging Unit Kit	Up to 60,000 pages⁵	108R01121	
	Waste Cartridge	Up to 30,000 pages⁵	108R01124	
	Fuser Assembly (110V)	Up to 100,000 pages ⁶	115R00088	
	Fuser Assembly (220V)	Up to 100,000 pages ⁶	115R00089	
	Transfer Unit Kit	Up to 100,000 pages ⁶	108R01122	
Accessories	550-sheet Feeder (Adjustable up to A4 / legal)	-	097S04664	
	Stand (Adds storage capacity for supplies, device stability, mobility and 13.1 in. of height)	-	497K14670	
	Wireless Networking Adapter		497K11500	
	McAfee Integrity Kit		320500665	
	Common Access Card Enablement Kit	-	498K17546	

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ Requires analog phone line.

⁴ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

^s Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode

⁶ Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

Build and configure your own Xerox® WorkCentre 6655 Colour Multifunction Printer at www.buildyourownxerox.com/connectkey.

For more information, visit us at www.xerox.com/office

©2015 Xerox Corporation. All rights reserved. Xerox @, Xerox and Design @, CentreWare @, ConnectKey @, Copier Assistant @, DocuShare @, Global Print Driver @, MeterAssistant @, Mobile Express Driver @, Scan to PC Desktop @, SuppliesAssistant @, WorkCentre and Xerox Secure Access Unified ID System @ are trademarks of Xerox Corporation in the United States and/or other countries. Mopria is a trademark of the Mopria Alliance. As an ENERGY STAR @ partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. Updated 7/15 BR10688 W62SS-011A

